



(SUBMIT IN TRIPPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **Las Cruces**  
Lease No. **000775 (b)**  
Unit **P.M. Robinson B (AR)**

RECEIVED

OCT 20 1960

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<b>XX</b>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 23, 1960

Well No. **38** is located **1900** ft. from **29E** line and **2830** ft. from **29E** line of sec. **27**  
**29E** (Range) **2830** (Meridian)  
**29E** (Twp.) **2830** (Meridian)  
**29E** (Range) **2830** (Meridian)  
**29E** (Twp.) **2830** (Meridian)  
**29E** (Range) **2830** (Meridian)  
**29E** (Twp.) **2830** (Meridian)  
**29E** (Range) **2830** (Meridian)  
**29E** (Twp.) **2830** (Meridian)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

RECEIVED

DETAILS OF WORK

AUG 29 1960

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate casing points, and all other important proposed work)

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

- 7-25-60 **WEL 21 - Log 6040-6110, 5/8" x 1" choke, no water cushion. Open 1 hr w/water blank, closed in 2 mins. Rec. 2' oily fluid, 30 min WIP 254, IPT 254, FPP 254, 60 min WIP 254.**
- 8-01-60 **WEL 22 - Log 6120-6190, 5/8" x 1" choke, no water cushion. Open 1 hr w/water blank. Gas to surface in 15 mins. TWT, rec. 4613' black salty sulphur water & 270' gas cut mud. 30 min WIP 253 1/2, IPT 299 1/2, FPP 219 1/2, 1 hr WIP 253 1/2.**
- 7-29-60 **6392B - Run electric logs, spotted 21 lbs cement plug 2/6000 to 6390, 12 lbs cement 2/3400-3800; 42 lbs cement 2/2900-3400; 25 lbs cement 2/1018-950; 15 lbs cement plug in collar. Set regulation 1/2" water. FINAL REPORT, WEL 22B - plugged & abandoned.**

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Stimuley Oil & Gas Company**

Address **900 E Broadway, Hobbs, New Mexico**

By \_\_\_\_\_

Title **Dist. Supt.**

Orig & Rec: USGS; cc:WFD, JM, F11a