


STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION
P. O. BOX 87501
SANTA FE, NEW MEXICO 87501



Form C-103
Revised 10-1-77

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-1266

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Marbob Energy Corporation	8. Farm or Lease Name State "I"
3. Address of Operator P.O. Drawer 217, Artesia, N.M. 88210	9. Well No. 16
4. Location of Well UNIT LETTER <u>P</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>29</u> TOWNSHIP <u>17S</u> RANGE <u>29E</u> NMPM.	10. Field and Pool, or Wildcat Grbg Jackson SR Q G SA
15. Elevation (Show whether DF, RT, GR, etc.) 3584' KB	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Plug back, different reservoir ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pulled rods & tbg, ran in hole w/casing scraper & 4 3/4" bit to 6100', pull out; ran in hole w/retainer & set @ 5907'; cement Abo perfs w/200 sax Halliburton Lite and squeezed to 4000#; left 100' of cement on top of retainer; pull out 2 7/8" tbg.; ran cement bond logs-top of cement @ 1859'; ran DSN log; ran in hole, set cement plug from 5200' to 4900'; Perforated 2733-3358'; acidized 3156-3358' w/1000 gal. 15% NE acid; acidized 2733-2940' w/1000 gal 15% NE acid, fraced w/5000 bbl. gelled water and 35,000# 12/20 sand. Perforated 2591-2635' and fraced w/5000 bbl gelled water, 15,000# 20/40 and 6800# 12/20 sand; perforated 2344-2494' and acidized w/1000 gal. 15% NE acid. Put well on pump 4/16/85.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Verdine Quince TITLE Production Clerk

DATE 4/24/85

APPROVED BY _____ TITLE _____

DATE APR 26 1985

CONDITIONS OF APPROVAL, IF ANY: