

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

JAN 28 1969

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State ☒ Fee ☐
5. State Oil & Gas Lease No.	E-9201

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER- ☐	7. Unit Agreement Name
2. Name of Operator Continental Oil Company	8. Farm or Lease Name State S-30
3. Address of Operator Box 960, Hobbs, N. Mex. 88290	9. Well No. 2
4. Location of Well UNIT LETTER F 2310 FEET FROM THE north LINE AND 1254 FEET FROM THE west LINE, SECTION 30 TOWNSHIP 17-S RANGE 29-E N.M.P.M.	10. Field and Pool, or Wildcat Empire Field
15. Elevation (Show whether DF, RT, GR, etc.) 3643 GR	12. County Colo.

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☒	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

In order to increase production, it is proposed to do the following remedial work:

Squeeze perfs. 6276' - 6300' with 250 sacks cement.

Drill out cement to 6288' & spot 250 gals. 15% LSTNE acid from 6288' to 6038'. Perforate from 6273' to 6284' with one glass jet shot per foot. Pump acid on spot into formation at 1 P.M.

If water percentage low, perf. from 6222' to 6258' with one J.S.F., and acidize with 1000 gals of 15% LSTNE. Place well on production

If water percentage high, run cement retainer & set at 6263'. Squeeze perfs

6273' to 6284'. Spot acid & perf. 6222' to 6258'. Treat perfs. with 500 gals. 15% LSTNE.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *M. E. Yeakley* TITLE *Adm. Section Chief* DATE *1-27-69*

APPROVED BY *W. A. Gessett* TITLE *OIL AND GAS INSPECTOR* DATE *JAN 28 1969*

CONDITIONS OF APPROVAL, IF ANY:

N.M. O.C.C. 3 Colo. File