

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 046044
Unit Leonard # 2

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT.....	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL.....	<input type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 28 1942

Well No. 2 is located 990 ft. from N line and 2310 ft. from E line of sec. 33
N 17 S 29 E N.M.P.M.
 (34 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Loco Hills Daly New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We expect to drill a well at the above location to a depth of approximately 2900', unless oil or gas in commercial quantities is encountered at a lesser depth. We propose to run 24 7/8" casing on the top of the salt or immediately above the top of the salt at approximately 400' and cement with 50 s.x of cement and circulate mud to the surface. If oil is encountered in sufficient quantities, we expect to set from 2250' to 3000' of 20 7/8" O.D. casing as an oil string and also cement with 100 sacks of cement and circulate mud to the surface.

We expect, also to abide by U. S. G. S. rules and regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Perry Petr. Co.
 Address 417 Petr. Bldg.,
Midland, Texas.

By Harvey E. Yates
 Title Agent, 602 Cr. Bldg.,
Artesia, New Mexico.