

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on changed plans	X

Laoco Hills, New Mex.
Place

10-30-45
Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Grayburg Oil Co. State B Well No. 2 in the
Company or Operator Lease
124th & 14th of Sec. 36, T. 17S, R. 29, N. M. P. M.,
Grayson Jackson Field, Eddy County.

The dates of this work were as follows: 7-27-45 to 10-30-45

Notice of intention to do the work was (was not) submitted on Form C-102 on _____ 19____

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Please see attached sheet

Witnessed by _____
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

_____ day of _____, 19____

Name _____

Position _____

Notary Public

Representing _____

Company or Operator

My commission expires _____

Address _____

Remarks:

Approved: 11-2-45

Name

Title

COPY

Grayburg - State B - Section 36-17-29 - NE/4 NW/4 - October 30, 1945

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

We drilled cement plugs and closed out to 3270'. Plugged back to 3259 feet hole dry. Ran 3150' of 7" 20# casing and cemented with 100 max cement and heavy mud to top. Let set 72 hours before drilling plug and testing cement.
Results: Hole dry.

Oil Natural: 4 barrels per day

Gun perforated formation 3245-55 feet with 40 holes; and 3160-70 feet with 40 holes. Ran 3249 feet of 2" tubing with hook wall packer at 3100 feet.

Acidize with 300 gallons acid 3200-59 feet. Results: Swabbed 4 barrels in 8 hours. Then acidized with 1000 gallons acid 3200-59 feet. Results; well swabbed 3 barrels per hour.

Re-Acidized with 3000 gallons acid. Results: Well flowed 136 barrels in 15 hours.

Re-Acidized with 6000 gallons acid. Results: Well flowed 103 barrels in 8 hours.

Total acid - 10300 gallons - used by Dwell, Inc.

7" cemented by Halliburton Oil Well Cementing Company

Work started September 27, 1945

Work Completed October 30, 1945

