

## NEW MEXICO OIL CONSERVATION COMMISSION

TEST 21

MOR 3

Santa Fe, New Mexico

COPY

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than thirty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-105 WILL NOT BE APPROVED UNTIL FORM C-106 IS PROPERLY FILLED OUT.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Allet Fair &amp; Pope, Inc.

805 W. Missouri

Artesia, New Mexico

Company or Operator

Address

State A

Well No. 64

N.W.S.W.

of Sec. 36

T. 17

Lease

R. 29E

N. M. P. M.

Loco Hills

Field

Bady

County

Well is 1650

feet south of the North line and

330

feet west of the East line of

Sec 36

If State land the oil and gas lease is No. E-2023

Assignment No.

If patented land the owner is

Address

If Government land the permittee is

Address

The Lessee is

Address

Drilling commenced September 8, 1945

Drilling was completed

November 18, 1945

Name of drilling contractor Glum &amp; Beadle

Address

Artesia, New Mexico

Elevation above sea level at top of casing 3562 feet

The information given is to be kept confidential until

19

## OIL SANDS OR SERIES

No. 1, from 3119

to

3256

No. 2, from

to

No. 2, from

to

No. 3, from

to

No. 3, from

to

No. 4, from

to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None

to

feet.

No. 2, from

to

feet.

No. 3, from

to

feet.

No. 4, from

to

feet.

## CASING RECORD

| SIZE   | WEIGHT PER FOOT | THREADS PER INCH | MAKE | AMOUNT | KIND OF | CUT & FILLED FROM | PERFORATED |    | PURPOSE |
|--------|-----------------|------------------|------|--------|---------|-------------------|------------|----|---------|
|        |                 |                  |      |        |         |                   | FROM       | TO |         |
| 8 1/4" | 28 1/2          | 8                | --   | 483    | Larkin  |                   |            |    |         |
| 7" OD  | 20 1/2          | 8rd              |      | 3092   | Float   |                   |            |    |         |
|        |                 |                  |      |        |         |                   |            |    |         |
|        |                 |                  |      |        |         |                   |            |    |         |
|        |                 |                  |      |        |         |                   |            |    |         |
|        |                 |                  |      |        |         |                   |            |    |         |
|        |                 |                  |      |        |         |                   |            |    |         |
|        |                 |                  |      |        |         |                   |            |    |         |

## MUDGING AND CEMENTING RECORD

| SIZE OF HOLE | SIZE OF CASING | WHEN SET | NO. BAGS OF CEMENT | METHOD USED | MUD GRAVITY | AMOUNT OF MUD USED |
|--------------|----------------|----------|--------------------|-------------|-------------|--------------------|
| 10"          | 8 1/4"         | 483      | 50                 | Halliburton |             |                    |
| 8 1/4"       | 7" OD          | 3092     | 100                | "           |             |                    |
|              |                |          |                    |             |             |                    |
|              |                |          |                    |             |             |                    |
|              |                |          |                    |             |             |                    |

## PLUGS AND ADAPTERS

Heaving plug—Material

Length

Depth Set

Adapters—Material

Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

| SIZE | SHELL USED | EXPLOSIVE OR CHEMICAL USED | QUANTITY | DATE    | DEPTH SHOT OR TREATED | DEPTH CLEANED OUT |
|------|------------|----------------------------|----------|---------|-----------------------|-------------------|
|      |            | 20% Acid                   | 2000 gal | 11-2-45 | 3219-56               | Total Depth       |
|      |            | " "                        | 3000 gal | 11-4-45 | " "                   | " "               |
|      |            | " "                        | 3500 Gal | 11-2-45 | " "                   | " "               |

Results of shooting or chemical treatment. First Acid treatment increased prod. from 1 1/2 bbls to 15 bbls per day, no increase from other treatments. Bar Lowell Pilot Survey, found acid going in top pay only. Tried three times to acidize lower pay with formation packer did not hold.

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to TD feet, and from 0 feet to 0 feet

Cable tools were used from 0 feet to TD feet, and from 0 feet to 0 feet

## PRODUCTION

Put to producing January 12, 1946

The production of the first 24 hours was 15 barrels of fluid of which 100 % was oil; %

emulsion; % water; and % sediment. Gravity, Be 36

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

Driller Driller

Driller Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this

Place

Date

day of 19

Name

Position

Notary Public

Representing

Company or Operator

My Commission expires

Address

501 - 3 1/2 1100

| FORMATION |                                         | IN FEET |  | FROM |  |
|-----------|-----------------------------------------|---------|--|------|--|
| 250       | Sand & Red Bed                          | 250     |  | 250  |  |
| 235       | Gym & Anhydrite                         | 235     |  | 235  |  |
| 172       | Red Bed & Anhy.                         | 137     |  | 172  |  |
| 275       | Red Salt                                | 207     |  | 275  |  |
| 295       | Anhydrite                               | 220     |  | 295  |  |
| 1215      | Anhydrite                               | 350     |  | 1215 |  |
| 1315      | Broken Anhydrite                        | 70      |  | 1315 |  |
| 1325      | Anhydrite & Shale                       | 80      |  | 1325 |  |
| 2058      | Anhydrite                               | 208     |  | 2058 |  |
| 2090      | Red Sand                                | 32      |  | 2090 |  |
| 2100      | Red Sand & Anhydrite                    | 10      |  | 2100 |  |
| 221       | Tan & Grey Dolomite                     | 70      |  | 221  |  |
| 2707      | Tan & Grey Dolomite                     | 22      |  | 2707 |  |
| 2714      | Tan & Grey Dolomite                     | 11      |  | 2714 |  |
| 2795      | Tan Dolomite                            | 13      |  | 2795 |  |
| 2815      | White Dolomite                          | 50      |  | 2815 |  |
| 2916      | Red to Pink Dolomite                    | 71      |  | 2916 |  |
| 2980      | White Dolomite                          | 61      |  | 2980 |  |
| 3009      | Buff Dolomite Trace Black Shale         | 29      |  | 3009 |  |
| 3033      | White Dolomite                          | 24      |  | 3033 |  |
| 3049      | White Dolomite & Cemented Grey Dolomite | 16      |  | 3049 |  |
| 3083      | " & Light Buff Dolomite                 | 34      |  | 3083 |  |
| 3100      | White Dolomite                          | 17      |  | 3100 |  |
| 3119      | White & Buff Dolomite                   | 19      |  | 3119 |  |
| 3140      | White & Buff Dolomite                   | 21      |  | 3140 |  |
| 3197      | White & Buff Dolomite                   | 57      |  | 3197 |  |
| 3208      | White & Buff Dolomite                   | 11      |  | 3208 |  |
| 3238      | White & Buff Dolomite                   | 30      |  | 3238 |  |
| 3256      | White & Buff Dolomite                   | 18      |  | 3256 |  |