

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or dexiation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
Cable tools were used from.....0.....feet to.....2771.....feet, and from.....feet to.....feet.

PRODUCTION

Injection
Put to ~~Pressure~~ August 1, 19.62..

OIL WELL: The production during the first 24 hours was.....barrels of liquid of which.....% was
was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....	
T. Salt.....510.....	T. Silurian.....	T. Kirtland-Fruitland.....	
B. Salt.....1020.....	T. Montoya.....	T. Farmington.....	
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....	
T. 7 Rivers.....	T. McKee.....	T. Menefee.....	
T. Queen.....2218.....	T. Ellenburger.....	T. Point Lookout.....	
T. Grayburg.....2727.....	T. Gr. Wash.....	T. Mancos.....	
T. San Andres.....	T. Granite.....	T. Dakota.....	
T. Glorieta.....	T.	T. Morrison.....	
T. Drinkard.....	T.	T. Penn.....	
T. Tubbs.....	T.	T.	
T. Abo.....	T.	T.	
T. Penn.....	T.	T.	
T. Miss.....	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	12		Sand	2360	2378		Lime
12	20		Cheet	2378	2452		Anhy
20	55		Red shale	2452	2469		Lime
55	70		Sand	2469	2614		Anhy
70	85		Gravel	2614	2625		Brown Lime
85	155		Sand Shale	2625	2635		Grey Lime
155	275		Red shale	2635	2727		Lime
275	315		Anhy	2727	2741		Sand
315	320		Sand	2741	2771		Lime
320	375		Anhy				
375	415		Shale				
415	430		anhy	T. D.	2771		
430	508		Shale				
508	835		Salt				
835	860		Anhy				
860	1020		Anhy				
1020	1615		Anhy				
1615	1725		Lime				
1725	2218		Anhy				
2218	2245		Red sand				
2245	2256		Anhy				
2256	2265		Lime				
2265	2274		Anhy				
2274	2288		Lime				
2288	2360		Anhy				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

August 28, 1962
Company or Operator.....NEWMONT OIL COMPANY.....Address.....300 Becker Bldg., Artesia, N.M.
ORIGINAL SIGNED BY
Name.....H. J. LEDBETTER.....Position or Title.....Superintendent.....

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

Checked by
Open 6.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

RECEIVED

WELL RECORD

AUG 30 1962

O. C. C.

ARTESIA, OFFICE

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEWMONT OIL COMPANY

(Company or Operator)

STATE "A"

(Lease)

Well No. 3, in SW 1/4 of SE 1/4, of Sec. 36, T. 17S, R. 29E, NMPM.

LOCO HILLS

Pool, EDDY

County.

Well is 1295 feet from South line and 2615 feet from East line

of Section 36. If State Land the Oil and Gas Lease No. is B-1778

Drilling Commenced June 25, 1962 Drilling was Completed July 30, 1962

Name of Drilling Contractor Tom Boyd

Address Artesia, New Mexico

Elevation above sea level at Top of Tubing Head 3554 The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 315 to 350 feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	14	N	458				Surface
4 1/2	9.5	N	2717				Oil string

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8 5/8	458	50			
	4 1/2	2717	100			

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation

Depth Cleaned Out