

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPlicate*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 025733

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Square Lake 12 Unit

8. FARM OR LEASE NAME

Tract 6B

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Square Lake C-SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

7 - 17S - 30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Kewanee Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 3786, Odessa, Texas 79760

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surfaceUnit E, 1980' from North line and 660' from West line of
Section 7, T-17S, R-30E, Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Spudded with rotary tools 11-12-69. Washed down old hole to 406'. Set 7", 20#, J-55, new casing @ 392' GL to tie into 10-3/4" csg cut off @ 312' & cemented w/275 sacks Class C w/12% gel & 1/4# flo-seal per sack & 50 sacks Class C neat. This 7" csg was set to shut off lost circulation zone @ 80'. Approved verbally by USGS Office 11-13-69. Tested 7" csg to 500 psi prior to drilling plug. No loss in pressure.

RECEIVED

NOV 17 1969

U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED

E. J. Starnes

TITLE

Division Superintendent

DATE

11-14-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

DATE

ACCEPTED FOR RECORD
NOV 17 1969
ACTING
District Engineer

*See Instructions on Reverse Side

NOV 18 1969

U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, N.M.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and is approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; rigid or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled; and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.