

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instructio
verse side)ATE*
on reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-05067

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gissler "B", Tract #5

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson, CB-SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 8-17S-30E

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

WINDFOHR OIL COMPANY

3. ADDRESS OF OPERATOR

1202 First National Bank Bldg., Fort Worth, Texas 76102

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

660' from north and 1980' from east lines of
Sec. 8-17S-30E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

On July 6, 1968, this well was plugged back from 2883 to 2877 with
hydromite. Ran 4½" casing to 2557 with a Larkin tension casing packer set on bottom.

On Nov. 20, 1968, the open hole was fraced with 17,220 gallons of Redi-frac
with 10,000# of sand. A plug of 1,000# of rock salt was used to make a 2-stage
treatment. Pressure was 2500 to 2700 psi. at an average injection rate of 16.7 BPM.
Before treatment well pumped 25 barrels of water per day with no oil. After treatment
well pumped 3 BO plus 5 BWPd.

RECEIVED

APR 22 1969

O. C. C.
ARTERIA, OFFICERECEIVED
APR 18 1969
U. S. GEOLOGICAL SURVEY
ARTERIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ralph L Gray

TITLE

Consultant

DATE

April 18, 1969

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
APR 21 1969
R. L. BECKMA

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.