

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN THE MANNER
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-029339 (A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Convert to Water Injection	7. UNIT AGREEMENT NAME Grayburg Jackson - S.A.
2. NAME OF OPERATOR WINDFOHR OIL COMPANY	8. FARM OR LEASE NAME Grayburg Jackson GB-SA
3. ADDRESS OF OPERATOR 1202 First National Bank Bldg., Fort Worth, Texas 76102	9. WELL NO. 17
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2,000' from East and 1980' from South lines of Sec. 13-17S-30E.	10. FIELD AND POOL, OR WILDCAT Grayburg Jackson GB-SA
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA Sec. 13-17S-30E	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒ **Convert to Water Injection**

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Preliminary conversion work was reported on form dated Aug. 15, 1967.

Subsequently, an umbrella bridge was set at 3305', and gravel and cal seal were used to plug back to 3288'. On Feb. 6, 1968, ran 14 joints (462') of 4½" O.D. 9.5# J-55 casing and cemented with 100 sacks of incor cement. Reversed out 9 barrels of cement. Top of liner is at 2826'. Tested top of liner with 1,000 psi. for 30 minutes, and pressure held. Cleaned out to 3480'. Ran 2-3/8" tubing internally coated with plastic and set packer at 2841'. Resumed water injection Feb. 13, 1968.

(Formerly Jackson "A" #3-X).

RECEIVED

FEB 15 1968

R. L. E.
DISTRICT OFFICERECEIVED
FEB 15 1968
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ralph L. Gray

TITLE

Consulting Engineer.

DATE

Feb. 15, 1968

(This space for Federal or State office use)

APPROVED

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

FEB 15

R. L. E.
DISTRICT OFFICE

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.