

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN INSTRUCTIONS
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.6. IF INDIAN, ALLOTTEE OR TRIBE NAME
IC 029338 (A)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Convert to Water Injection	7. UNIT AGREEMENT NAME Grayburg Jackson S.A. Unit
2. NAME OF OPERATOR WINDFOHR OIL COMPANY	8. FARM OR LEASE NAME Grayburg Jackson, GB-SA
3. ADDRESS OF OPERATOR 1202 First National Bank Bldg., Fort Worth, Texas 76102	9. WELL NO. 11
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' from south and east lines of Sec. 14-17S-30E.	10. FIELD AND POOL, OR WILDCAT Grayburg Jackson, GB-SA
11. SEC., T.P., R., OR B.L. AND SURVEY OR AREA Sec. 14-17S-30E	12. COUNTY OR PARISH Eddy
13. STATE New Mexico	

14. PERMIT NO. 17 1968	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	
SUBSEQUENT REPORT OF:	
WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Convert to water injection	
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	

Preliminary conversion work was reported on form dated Aug. 15, 1967.

Subsequently, the hole was plugged back with gravel to 3414' and to 3408' with hydromite. An umbrella bridge was set at 3350' with 4' of gravel and cal seal back to 3334'. On Dec. 11, 1967, ran 16 joints (521') of 4½" O.D. 9.5# J-55 casing liner and cemented with 120 sacks of incor cement. Reversed out 13 barrels of cement. Top of liner is at 2813'. Tested top of liner with 1,000 psi. and pressure held 30 minutes. Drilled out plugs to 3408'. Resumed water injection on Dec. 20, 1967. A packer is set at 2825' on 2" tubing internally coated with plastic.

(Formerly Gissler "A" #4)

18. I hereby certify that the foregoing is true and correct

SIGNED

*Ralph L. Gray*TITLE **Consulting Engineer.**

(This space for Federal or State office use)

APPROVED

COMMITTEES OF APPROVAL, IF ANY:

TITLE

DATE

RECEIVED
FEB 6 1968
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO
DATE Feb. 6, 1968

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

ORIGINAL