

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029338(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Grayburg Jackson S.A.

8. FARM OR LEASE NAME

9. WELL NO.

21

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson, GB-SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 14-17S-30E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒

Water Injection

2. NAME OF OPERATOR

WINDFOHR OIL COMPANY

3. ADDRESS OF OPERATOR

1202 First National Bank Bldg., Fort Worth, Texas 76102

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface 1650' from south and east lines of Sec. 14-17S-30E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Convert to Water Injection ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

An umbrella bridge was set at 3214'. Gravel was dumped from 3214' to 3209'. Cal seal was placed from 3209' to 3198'. On July 16, 1969, a 4½" O.D. 9.5# J-55 liner was cemented from 3198' to 2790' with 100 sacks of Incor cement. Top of liner was tested with 1500 psi. for 30 minutes and pressure held. Plugs were drilled out and hole cleaned to 3425' on July 18, 1969. 2-3/8" O.D. upset tubing internally lined with cement was run and a tension packer was set at 2810'. Water injection was resumed on July 23, 1969.

RECEIVED

JUL 20 1969

D. C. C.
ARTEBIA, OFFICE

RECEIVED

JUL 25 1969

18. I hereby certify that the foregoing is true and correct

SIGNED

Ralph L Gray

TITLE

Consultant

DATE

July 25, 1969.

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL ONLY

TITLE

DATE

ACCEPTED FOR RECORD
JUL 28 1969

Date

ACTING District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.