


Form 9-331a
(Feb. 1951)

APPROVED

FEB 15 1965

(SUBMIT IN TRIPLICATE)

 UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY
 ACTING DISTRICT ENGINEER

Land Office

Lease No. **LC 029020** (L)

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. **1** is located **1650** ft. from **N** line and **1650** ft. from **E** line of sec. **13**

N 1/2 (1/4 Sec. and Sec. No.) **17N** (Twp.) **30E** (Range) **104N** (Meridian)

Grayburg Jackson (Field) **Kddy** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **3697** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to set a retrievable bridge plug at 3070', perforate 4 1/2" casing from 3003'-07' and 3016'-26', acidize with 500 gallons acid, free with 20,000 gals. slick water and 40,000 gals. sand and test. If results of test are unsatisfactory we propose to perforate from 2965' to 2998' and re-test.

FEB 16 1965

D. C. C.
ARTEZIA, OFFICE

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Graridge Corporation**Address **Drawer B****Artesia, New Mexico**By **Thomas E. Lee**Title **Dist. Superintendent**