

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Etz Oil Company

Roswell, New Mexico

Company or Operator

Address

Etz-State

Well No. 2 in NW SW of Sec. 16, T. 17

Lease

R. 30

N. M. P. M.

Grayburg

Field,

Eddy

County.

Well is 1980 feet south of the North line and 2640 feet west of the East line of section 16

If State land the oil and gas lease is No. B-2209

Assignment No. 7

If patented land the owner is

Address

If Government land the permittee is

Address

The Lessee is

Address

Drilling commenced February 19 19 36

Drilling was completed July 11, 19 36

Name of drilling contractor K&K Drilling Co.

Address Roswell, New Mexico

Elevation above sea level at top of casing 3667 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES					
No. 1, from	2075	to	2105	No. 4, from	3185 to 3195 Increase in oil
No. 2, from	2717	to	2721 show	No. 5, from	
No. 3, from	3140	to	3247 Oil 2500' in hole	No. 6, from	

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 392 to 395 feet.

No. 2, from raised about 50 ft. in hole, 2 balers per hour.

No. 3, from to feet.

No. 4, from to feet.

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 1/4	32	8	Nat.	1320	drive				
6 1/4	20	10	Ches-	2565	drive				
			ter						
			Lap-						
			weld						

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"						
	8 1/4"	1320'	25	Dumped baler	10#	Mud to surface
	6 1/4"	2565'		Landed		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Dowell X	2000 gal	7-15-36	3130-3276	3276

Results of shooting or chemical treatment Estimated 60 bbl per day before treatment, 1st 24 hrs after treatment 60 bbls, acid treatment didn't increase oil.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 9 feet to 3276 feet, and from feet to feet

PRODUCTION

Put to producing July 11, 19 36

The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

H. W. Etz Jr., Driller J. W. Jones, Driller

K. R. Swanberg, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 28th day of July 19 36

SEAL T. J. Jackson Notary Public

Roswell, New Mexico July 20, 1936

Place Date

Name George Etz

Position

Representing Etz Oil Company

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	5		Sand
5	30		Gyp
30	130		Red sand and red beds
130	255		Red rock and red shale
255	310		Gyp & red bed
310	325		Gyp
325	360		Anhy
360	392		Red bed, gyp
392	395		Salt water- 2 balers per hour
395	410		Gyp and red rock
410	440		Red shale
440	460		Gyp
460	527		Red beds and gyp
527	990		Salt
990	1010		Anhy
1010	1070		Gyp, salt and red rock
1070	1600		Anhy
1600	1655		Lime shells
1655	2075		Anhy, red rock, red shale, lime shells
2075	2105		Red sand --black oil
2105	2440		Anhy
2440	2276		Lime
2276			Total depth dark brown line 3270