

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

MAR 13 1972

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. B-2209	
7. Unit Agreement Name	
8. Farm or Lease Name Etz A State	
9. Well No. 2	
10. Field and Pool, or Wildcat Grayburg Jackson	
12. County Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Water Injection
2. Name of Operator Texas American Oil Corporation
3. Address of Operator 1012 Midland Savings Building, Midland, Texas 79701
4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 17-S RANGE 30-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3667 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug and abandon as follows:

- (1) Cement plug from ¹⁴⁵⁰1926' to ²⁰⁵⁰2026' in bottom of 7" casing.
- (2) Cement plug at base of salt 990' to 1090'.
- (3) Cement plug at top of salt 450' to 550'.
- (4) Cement plug at surface to 10' with standard marker.

Plan to knock off 7" and 8-5/8" casing at top of cement and pull.

* Intervals between plugs filled w/ mud

Notify N.M.O.C.C. in sufficient time to witness

Plugging operations

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *J. C. Ensmull* TITLE Engineer DATE March 10, 1972

APPROVED BY *W. A. Gussert* TITLE OIL AND GAS INSPECTOR DATE MAR 14 1972

CONDITIONS OF APPROVAL, IF ANY:

*