

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Roswell, New Mexico.  
PlaceMarch 19, 1942.  
DateOIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Etz Oil Company, Inc. Etz-State-Humble Well No. 5 in the  
Company or Operator Lease  
SE SW NE SE of Sec. 16, T. 17S, R. 30E, N. M. P. M.  
Grayburg-Jackson Field, EDDY County

The dates of this work were as follows: Started January 26, 1942; completed February 18, 1942

Notice of intention to do the work was (was not) submitted on Form C-102 on 11-14-41 &amp; 1-26-42 19

and approval of the proposed plan was ~~was not~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

We run 30 feet 10# mud from 3300' to 3270'; then 30 feet cement from 3270' to 3240'; then mud to 3140'; then cement from 3140' to 3110'; then mud to 2530. We shot the 7" OD at 2400' with 4 quarts nitro-glycerin-unable to pull; shot the 7" again at 2250' with 4 quarts nitro glycerin--7" pulled in two at 1600'. This 1600' casing was recovered. We run mud 2530' to 1665'; then 5 feet cement to 1650'; then mud to 500'. We shot the 8 1/4" at 380' with 4 quarts nitro glycerin and pulled this pipe. We left 928'-7" OD casing in the hole from 1600' to 2528'. We left 118'--8 1/4" in the hole from 380' to 498'. We completed mudding to surface, and set steel marker in concrete. H. W. Etz, Jr.-Lease Superintendent, Box 213, Loco Hills, N. Mexico. and Walter Solt, Artesia, N.M. were in charge Company of the work. Title

Subscribed and sworn before me this 20

day of March, 19 42

(Signed) T. J. Jackson

Notary Public

My commission expires February 29, 1944

I hereby swear or affirm that the information given above is true and correct.

(Signed)  
Name A. N. Etz

Position Secretary

Representing Etz Oil Company, Inc.  
Company or Operator

Address Box 992, Roswell, New Mexico

Remarks:

(Signed) Roy Yarbrough.  
NameOil & Gas Inspector.  
Title

10-22-02

~~NO~~ SRC - TO HAVE  
FRAN DELETE IN  
ONGARD

---