

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-8095

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Harlan Production Company	8. Farm or Lease Name Etz C State
3. Address of Operator P.O. Box 355, Monahans, Texas 79756	9. Well No. 7
4. Location of Well UNIT LETTER F 2310 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 17 RANGE 30 NMPM.	10. Field and Pool, or Wildcat Grayburg Jackson
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to bridge hole back to 2065 with gravel. Cement $4\frac{1}{2}$ " blank liner from 1850 to 2065 with 75 sacks regular cement and 75 Cu. ft. Perlite. Test liner and squeeze if necessary before drilling out. Clean out to 2110 T.D. Sand Frac with 17,000# sand.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *E. L. Emanuel* TITLE Petroleum Engineer DATE 4/12/68

APPROVED BY *R. L. Stam* TITLE OIL AND GAS INSPECTOR DATE APR 15 1968

CONDITIONS OF APPROVAL, IF ANY: