

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 074936

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McIntyre

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 17, T-17S, R-30E NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Kennedy Oil Co., Inc.

3. ADDRESS OF OPERATOR

Box 151 Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface330° PSL Sec. 17, T-17S, R-30E NMPM
1650° FEL (SW/4 SE/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3666 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐(Other) PerforateREPAIRING WELL ☒ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

PERFORATED:	Lovington Sand	2861-64	12-.41 jets
	Vacuum Lm.	2785-87	12 " "
	Loco Hills	2489-91	4 " "
	" "	2908-12	8" " "

Used Halliburton bridge plug and packer to treat the above zones.

Frased Lovington Sand (2861-64) with 20,000 gal. HF-40 gelled water & 20,000 #s
of 20-40 sand. 3000 max. pr. @ 14 BPM.

Acidized Vacuum (2785-87) with 1000 gal. 15% acid & 3000 gal. 20% acid.

Frased Loco Hills (2489-2512) with 30,000 gal. HF-40 gelled water & 30,000 #s
20-40 sand. Max. pr. 2200 psi @ 18 BPM.Ran 2355' of 4 1/2" 9.5 used casing with a Gullerson 2-cup packer, and cemented with
250 cu. ft. of cement. Est. top of cement from pump pressure was 50-100 ft.

RECEIVED

JUL 5 1972

O. G. I.
ARTESIA, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

V.P.

DATE

6/29/72

(This space for Federal or State office use)

TITLE

DATE

*See Instructions on Reverse Side

APPROVED

JUL - 3 1972

R. L. BEEKMAN

ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

RECEIVED
JAN 10 1964
U.S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
WASHINGTON, D.C.