Form 3160-5 (June 1990)

DEPARTMENT OF THE INTERIOR RECEIVED UNITED STATES

FORM APPROVED
Budget Bureau No. 1004-013:
Expires: March 31,1993

BUREAU OF LAND MANAGEMENT 5. Lease Des SUNDRY NOTICES AND REPORTS ON WELLS 2 Do not use this form for proposals to drill or to deepen or mentry to a different reservoir. 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT—" (GARES 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE I Type of Well RECEIVED Oil Well Other 8. Well Name and No 2. Name of Operator McIntyre DK Federal #3 Mack Energy Corporation 9. API Well No. 3. Address and Telephone No 30-015-04186 (505)748-1288 P.O. Box 960, Artesia, NM 88211-0960 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T. R., M. or Survey Description) Grayburg Paddock 11. County or Parish, State 660 FSL 1980 FWL Sec 17 T17S R30E Eddy, NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Conversion to Injection Deepening, Run 4 1/2" Csg Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work) 5/01/97 Rig up, pull rods, pump and 2 3/8" tubing. RIH with 6 1/4" tooth bit, drill collars, 2 7/8" workstring, clean some iron and fill to

bottom, start new hole drilling formation to 3438, POH with tooth bit.

5/02/97 RIH with button bit drilling 6 1/4" hole form 3438' to 3912'.

5/05/97 Drilling from 3912' to 4355' 6 1/4" hole.

5/06/97 Drilling from 4355' to 4797', TD 6 1/4" hole @ 4797

5/07/97 RIH with bit, no fill pump brine water 130bbls, and 180bbls mud mix spot on bottom, POH laying down, Rig up Schlumberger to run logs.

5/08/97 Ran in hole with 106 joints 4 1/2" 11.60#, J-55, LT&C casing. Landed casing at 4782', DV tool @ 4005', Mk. Jt. @ 3640', Cemented 1st stage cement with 100 sacks 50/50 Poz, 2% CaCl, circ. 20 sks. off DV Tool, circ. 6 hrs. Cemented 2nd stage with 200 sacks 50/50 Poz, 2% CaCl, tie back into 7" csg. WOC.

Signed	of the state of going is true and the state of the state		Title	Vice President	Date	5/9/97
Approved	CEPTED FOR RECOR RIG. SGD.) DAVID Cappioval, if any LIA 1 4 1997	R. GLAS	Title		Date	
Title 18 U.S.C. S	ection 100], makes it a crime for	any person kn	owingly and willfully to m	ake to any department or agency of the Unit	ed States any false, fictiti	ous or fraudulent statements