30-015-04214

OGRID 13837

PROP 6125

POOL 96121 - SWD SAN ANDRES

9-22-99
PLATFORM EXPRESS/THREE DETECTOR LITHO-DENSITY/COMPENSATED NEUTRON INGT
3,002' - 4,770'

PLATFORM EXPRESS/AZIMUTHAL LATEROLOG MICRO-CFLINGT
3,002' - 4,780'

IT IS THEREFORE ORDERED: [redacted] 5175 3-8-78 O.C.D. 5671 3-14-78

(1) That the applicant, Petroleum Corporation of Texas, is hereby authorized to utilize its Jenkins "B" Fed. Well No. 1, located in Unit E of Section 20, Township 17 South, Range 30 East, NMPM, Grayburg-Jackson Pool, Eddy County, New Mexico, to dispose of produced salt water into the San Andres formation, injection to be accomplished through 2 3/8-inch tubing installed in a packer set at approximately 2950 feet, with injection into the open-hole interval from approximately 3000 feet to 3258 feet;

PROVIDED HOWEVER, that the tubing shall be plastic-lined; that the casing-tubing annulus shall be filled with an inert fluid; and that a pressure gauge shall be attached to the annulus or the annulus shall be equipped with an approved leak detection device in order to determine leakage in the casing, tubing, or packer.

(2) That the injection well or system shall be equipped with a pop-off valve or other acceptable device which will limit the wellhead pressure on the injection well to no more than 600 psi.

(3) That the operator shall notify the supervisor of the Artesia district office of the Commission of the date and time of the installation of disposal equipment so that the same may be inspected.

(4) That the operator shall immediately notify the supervisor of the Commission's Artesia district office of the failure of the tubing, casing, or packer, in said well or the leakage of water from or around said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

(5) That the applicant shall submit monthly reports of its disposal operations in accordance with Rules 704 and 1120 of the Commission Rules and Regulations.

Geol. Tops per/BGA

Glorieta 4150

Re-Order

Ennis FILE FOLDER

21-1/3DU

Geol. Tops per/BGA

Glorieta 4150