

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960

4. Location of Well (Footage, Sec., T. R., M. or Survey Description)

1650 FSL & 410 FEL, Sec. 20, T17S R30E, 1

5. Lease Designation and Serial No.

LC-054280

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

8. Well Name and No.

McIntyre A #4

9. API Well No.

30-015-04222

10. Field and Pool, or Exploratory Area

Loco Hills Abo

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

Mack Energy Corporation proposes to plug and abandon well as follows:

1. Notify BLM 24 hours before starting plugging operations.
2. RIH tag CIBP @ 6658', set 35' cement cap.
3. Circulate hole w/mud.
4. Set 100' cement plug from 3950-3850' top of San Andres zone.
5. Set 100' cement plug from 1910-1810' 50' above and below bottom of 8 5/8 casing.
6. Set 100' cement plug from 580-480' 50' above and below top of salt.
7. Set 60' surface plug.
8. Install dry hole marker.

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

APPROVED

SEP 23 2002

LES BABYAK
PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct

Signed

Curtis D. Lat

Title

Production Analyst

Date

9/13/02

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

•See Instruction on Reverse Side