

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 054280

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McIntyre A

9. WELL NO.

5A

10. FIELD AND POOL, OR WILDCAT

San Jackson
Loco Hills Abo11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20-17S-30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

FRANKLIN, ASTON & FAIR, INC.

3. ADDRESS OF OPERATOR

P. O. Box 1090, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

990' FSL and 410' FEL. Sec. 20, T. 17 S., R. 30 E., NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3645' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On January 23, this well was recompleted as follows:

Wire line bridge plug with 35' cement was set at 6730' to seal off Abo perforations 6742' - 6798'. Another wire line bridge plug with 35' cement was set at 3545'. The San Andres Jackson pay was perforated at selective intervals from 3398' - 3446'. Production from this zone has decreased 6 BO + 2 BWPD and is no longer economical to produce. After telephone conversation with Mr. Knauf, we plan to P & A this well as follows.

25 sack cement plug across perms 3398' - 3446'.
10' cement plug and marker at surface.

No casing will be pulled:

8 5/8" casing was set at 1873' w/580 sacks cement
5 1/2" casing was set at 6830' w/750 sacks cement temperature shows cement 100' below surface.

RECEIVED

MAY 6 - 1970

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

Grant M. Smith

TITLE Geologist

DATE May 4, 1970

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

R. L. BECKMA

*See Instructions on Reverse Side