

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

RECEIVED

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960

4. Location of Well (Footage, Sec., T. R., M. or Survey Description)

330 FNL 330 FEL Sec 20 T17S R30E

5. Lease Designation and Serial No.

LC-029342-C

6. If Indian, Allottee or Tribe Name

7. Unit or CA, Agreement Designation

8. Well Name and No.

W D McIntyre C #2

9. API Well No.

30-015-04226

10. Field and Pool, or Exploratory Area

Grayburg Paddock

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☒ Altering Casing

☐ Other

Deepening, Run 4 1/2" Csg

☐ Completion of P

☐ New Construction

☐ New Routine Fracturing

☐ Well Shut-Off

☐ Completion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion, Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

4/22/97 Rig up, pull rods, pump and 2 3/8' tubing, shut down.

4/23/97 RIH with 6 1/4" Tooth bit and Jet Sub 20- 4 3/4" drill collars and 2 7/8" workstring, Clean out to 3265' and Drilled to 3311'.

4/24/97 Drilling @ 3785'.

4/25/97 Drilling @ 4165'.

4/26/97 Drilling @ 4576'.

4/28/96 Drilling @ 4858'. TD 6 1/4 hole @ 4858'. Pump 130 bbls. brine, 130 bbls of mud mix with gel and starch. POH laying down workstring, drill collars, Rig up Schlumberger Log Well.

4/29/97 Ran in hole with 108 joints 4 1/2" 11.6#, J-55, LT&C casing. Landed casing @ 4824', & DV Tool @ 4008', MK Jt @ 3738'.

Cemented 1st stage with 110 sacks 50/50 C Poz, 2% gel, .5% FL-25, 5# salt. Circ 26 sacks. Cemented 2nd stage with 250 sacks 50/50 C Poz, 2% gel, .5% FL-25, 5# salt. WOC.

14. I hereby certify that the foregoing is true and correct

Signed

Robert C. Chan

Title

Vice President

Date

5/9/97

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: