

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Repollo Oil Company Hobbs, New Mexico
Company or Operator Address
W. D. McIntyre Well No. 3 in E 1/2 NE of Sec. 20, T. 17
Lease
R. 30 N. M. P. M. Artesia Field, Eddy County.
Well is 990 feet north of the North line and 330 feet east of the East line of Section 20
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is Address
The Lessee is Address
Drilling commenced May 17 19 38 Drilling was completed July 8 19 38
Name of drilling contractor Address
Elevation above sea level at top of casing 3650 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3190 to 3300 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8	32#	8		504	TP				
7" OD	24#	10		2904	Float				
2" Reg. Tubing				3267					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8 5/8	504	50	Halliburton		
	7" OD	2904	100	Halliburton		5 Ton

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
Acidized W/	1500 Gallon Dowell	"XX"	Acid on	July 10th		

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 3300 feet, and from feet to feet

PRODUCTION

Put to producing 7-16-38 19
The production of the first 24 hours was 278 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Ray Edge Driller Geo. Sands Driller
K. R. Swanberg Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 13th Hobbs, New Mexico
day of July 19 38 Name L. Surret

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	315		Red rock
315	495		Anhy
495	1095		Salt
1095	2450		Anhy
2450	3300		Lime
3300			Total depth