

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	FORM APPROVED FORM APPROVED	
1301 W.	Grand Avenue 7022	_

BUREAU OF L	AND MANAGEMENT 1301 V	V. Grand Avenue 67932
Do not use this form for proposals to dri	AND REPORTS ON WELLS If or to deepen or reentry to a different rese R PERMIT—" for such proposals	All Iran All Otee or Tribe Name
SUBMIT	7. If Unit or CA, Agreement Designation	
I Type of Well Sil Gas Well Other		8. Well Name and No. W D McIntyre E #2
3. Address and Telephone No.	nergy Corporation Artesia, NM 88211-0960 (505)748-12	9. API Well No. 30-015-04228
4. Location of Well (Footage, Sec., T. R., M. or Survey De	FWL, Sec. 20 T17S R30E	Grbg Jackson SR Q Grbg SA 11. County or Parish, State Eddy, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, F	REPORT, OR OTHER DATA
Notice of Intent Subsequent Report Final Abandonment Natice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
give subsurface locations and measured and true verti	7" production casing from 2738'-2638' こみ とっ nd squeeze 100' cement plug. queeze 100' cement plug.	

APPROVAL SUBJECT TO GENERAL REQUIREMENTS AND SPECIAL STIPULATIONS ATTACHED

14. I hereby certify that the foregoing is rue and correct Signed Levy W. Sharrel	Title_	Production Clerk		2/25/02
(This space for Federal or State office use) (ORIG. SGD.) ALEXIS C. SW Approved by Conditions of approval, if any:	OBODA Title	PETROLEUM ENGINEER	Date	FEB 28 2002
Accepted for record only MAR 5 2002		to make to any department or agency of the United State	es any false, fio	ctitious or fraudulent statemer

BUREAU CHEAU MGMT BUREAU CHEAU

2002 FEB 27 AM 8: 36

BECEINED

Mack Energy Corporation W D McIntyre E #2

After

Before

522' w/50sx 8 5/8 casing set @ 2688'-3280' Open hole from w/100sx7" casing set @ 2688' 522' w/50sx 8 5/8 casing set @ circulate to surface Perforate 7" @ 60' and W/100sxPerforate 7" @ 550 top 7" casing set @ 2688' cement squeeze 100sx cement of salt and squeeze 100sx 2688'-3280' bottom of salt and Perforate 7" @ 990' Open hole from above and below bottom of Set 100' cement plug 50' 7" casing.

TM6 / C. A. U. ABFUG EOHRO JJBW809

2002 FEP 27 AM 8:36

BECEINED