

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

E*
re-

Form approved
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC 029342 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL GAS WELL OTHER Dry Hole

7. UNIT AGREEMENT NAME

Loco Hills Morrow

2. NAME OF OPERATOR

Franklin, Aston & Fair, Inc.

JUN 4 1975

8. FARM OR LEASE NAME

Woolley

3. ADDRESS OF OPERATOR

P. O. Box 1090, Roswell, New Mexico 88201 O. C. C.

9. WELL NO.

2

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1750' FWL & 890' FSL

10. FIELD AND POOL, OR WILDCAT
South Loco Hills Morrow

11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA

Sec. 21-T17S-R30E, N.M.P.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3627 GR

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO :

SUBSEQUENT REPORT OF :

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On August 1, 1974, this well was plugged and abandoned as follows:

- 50 sack cement plug 10,800-10,650' at top of Morrow formation.
- 50 sack cement plug 9,225- 9,075' at top of Canyon formation.
- 50 sack cement plug 8,000 -7,850' at top of Wolfcamp formation.
- 50 sack cement plug 6,875 -6,725' at top of Abo formation.
- 50 sack cement plug 4,600 -4,450' at top of Glorietta formation.
- 50 sack cement plug 3,650 -3,500' in and out base of 8 5/8" casing.
- 10 foot cement plug with marker at surface.

Cementing work done by Halliburton with Type H neat cement.

RECEIVED

AUG - 7 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Grant M. Smith

TITLE Geologist

DATE August 1, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 3 - 1975
L. BEEKMAN
ACTING DISTRICT ENGINEER

posted
ID-2
27-75

*See Instructions on Reverse Side