

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER DRY HOLE

2. NAME OF OPERATOR
FRANKLIN, ASTON & FAIR, LTD.

3. ADDRESS OF OPERATOR
P. O. BOX 1090, ROSWELL, NEW MEXICO 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
990 FWL - 2100 FSL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)
3,647 GR

5. LEASE DESIGNATION AND SERIAL NO.
NM 0467930

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
LOCO HILLS MORROW

8. FARM OR LEASE NAME
SINCLAIR

9. WELL NO.
#1 (RE-ENTRY)

10. FIELD AND POOL, OR WILDCAT
SOUTH LOCO HILLS MORROW

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 22 - 17S - 30E

12. COUNTY OR PARISH
EDDY

13. STATE
NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data:

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

This well was plugged back from 11436 feet to 9380 feet; 4 1/2 inch casing was set at 9380 feet and cemented to 8600 feet with 100 sacks cement. The Cisco was perforated from 9244 feet to 9254 feet and acidized with 7,500 gallons acid. After an additional 1,500 gallons acid treatment, the well swabbed dry. After telephone conversation with Mr. Knauf, we plan to plug and abandon as follows:

25 sack cement plug 9100 feet to 9300 feet across perforations and top of Cisco 9205 feet. Shoot 4 1/2" casing at approximately 8600 feet;

35 sack cement plug 7900 feet to 8050 feet, top of Wolfcamp 8020 feet;

50 sack cement plug 6650 feet to 6800 feet in 7 7/8 hole, top Abo 6695 feet;

50 sack cement plug 4500 feet to 4650 feet in 7 7/8 hole, top Glorietta 4615 feet;

50 sack cement plug 3150 feet to 3300 feet in 7 7/8 hole, top San Andres 3220 feet;

50 sack cement plug 2050 feet to 2250 feet in and out base of 7 inch casing 2150 feet;

10 sack cement plug and marker at surface.

18. I hereby certify that the foregoing is true and correct

SIGNED Grant M. Smith

TITLE Geologist

DATE March 11, 1976

(This space for Federal or State office use)

APPROVED BY APPROVED
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side