

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Repollo Oil Company

Hobbs, New Mexico

Company or Operator

Address

D.H. Parke^{1st}

Well No. 3

in NW NW

of Sec. 22

T. 17 S

Lease

R. 30E

N. M. P. M.

Artesia

Field,

Eddy

County.

Well is 330 feet south of the North line and 330 feet west of the East line of Section 22

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced 4-21-38 19 Drilling was completed 6-13-38 19

Name of drilling contractor Address

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3194 to 3345 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8"	28	8		524	TP				
7" OD	24	10		2904	Float				
2"	4.6	Reg. 88		3240	Tubing				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8 5/8"	524	50	Halliburton		
	7" OD	2906	100	Halliburton		7 Ton

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
Acidized W/	1000 Gallon Dowell	"XX"	6-15-38	F/	3180-3345	

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 3345 feet, and from feet to feet

PRODUCTION

Put to producing 6-16-38 19

The production of the first 24 hours was 157 barrels of fluid of which 100 % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

W.F. McCullough Driller J.E. Edwards Driller

J. Thompson Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this

Hobbs, New Mexico

Place Date

day of 19

Name F. Brett

Position District Supt.

Notary Public

Representing Repollo Oil Company

Company or Operator

My Commission expires

Address Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	345		Sand and red rock
345	524		Anhy
524	595		Anhy and red rock
595	1055		Salt
1055	2535		Anhy
2535	3345		Lime
3345			Total depth