## N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## **WELL RECORD**

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

LQCA	TE WELD	L COR	RECTLY								
	Repol		Oil Co				Ŧ	ulsa,	Oklah	noma	
_r_a_	Domire		мрану от О	_	F.	4- 3773		~	Address	מר	
		•							-	, т17	
				Arte			~ ~ <b>* +</b>	***	+		County
						OUfeefXi	Keat of the	heXBoxt li	ine of	section	<del></del>
				is No							
				6							1939
				of casing			,				
The info	rmation s	given	is to be ke	pt confidenti	al until		<del></del>			19	
					OIL SAN	DS OR ZON	TES				
No. 1, fr	om. 32	330		to 324	0	No. 4, f	rom			_to	1 - 42
No. 2, fr	om32	283		to330	0	No. 5, f	rom	<del></del>		_to	
No. 3, fr	o <b>m</b>			.to		No. 6, f	rom			to	<del> </del>
				T.	MPORTAN'	T WATER	SANDS				
Include o	data on r	ate of	water inf	low and ele	vation to w	hich water	ros <b>e in h</b>	ole.			
No. 1, fr	om			<del></del>	.to			fee	t		<del></del>
No. 4, fr	o <b>m</b>				_to			fee	t		
					CASI	NG RECORI	)				
	weig	HT	THREADS			KIND OF		FILLED	PER	FORATED	PURPOSE
SIZE	PER F		PER INCI	I MAKE	AMOUNT	SHOE	FRO		FROM	то	
3 5/8 7 "OD	4	_	8		<u>540</u>	TP	Ü				
	Tubir	, ,	10 8		2918 3295	Float W/ Amer		F1 000	Paglant	r @ 2840	
	L				· · · · · · · · · · · · · · · · · · ·	<u> </u>	<u> </u>		<del></del>		
				MUDD	ING AND	CEMENTIN	G RECO	RD			
SIZE OF HOLE	SIZE OF CASING	wo	CRK SKT	NO. SACKS OF CEMENT	n herama	700 0000				T.	
		<b></b> -				HOD USED	Mil	UD GRAVI	TY	AMOUNT OF M	UD USED
	<del>8 5/3</del> 400		540	75		burton	<del> </del>				
	<del> (20</del>	<del>29</del>	24	1-90	Hall1	burton	<del> </del>			7 ton	
					PLUGS A	ND ADAPTI	ERS				
Heaving	plug—M	ateria	L		Length	·			Depth Set	t	
Adapters-	—Materi	aL		·	Size						
			REC	ORD OF S	HOOTING	OR CHEM	CAL T	REATME	NT		
		<del></del> -	EXF	PLOSIVE OR				DEDMI	CATOR		<del></del>
SIZE	SHEL	l use	D CHÈ	MICAL USED	QUANS	PITY DA	DATE DEPTH S OR TREA				
cidiz	ed-W	/ 3	OGO Gal. Dowel		11 "XX"	F/ 322	3220 to 3		} 		
			<del>- </del>								
					!			<u> </u>		<u> </u>	
Results o	f shootin	g or	chemical t	reatment							<del></del>
								<del></del>			
										<del>v</del>	
f drill-at	om on ot	han an		RECORD O							
i um-so	em or ou	ner sp	eciai tests	or deviation	ı surveys w	ere made, s	ubmit re	eport on	separate :	sheet and atta	ch hereto.
		_				LS USED					
totary to	ools were	used	from	fe	et to	feet	, and fr	om	f	eet to	feet
abie too	ois were	used	irom	fe	et to	feet	, and fr	om	f	eet to	feet
			~ *	F7 0		DUCTION					
ut to pro	oducing_	43	12	-39	19	<del></del>					
										% was oil;	
							asoline p	per 1,000	cu. ft. of	gas	
Pres	u.o, 198	. Per	տալ, <u>եԱ,</u>								
	_		, .	3.5		LOYEES		•			
								<b>~</b>			
	K.	_t,	owanb	erg	, Drill	er	Sand	u <b>s</b>	······································	<del></del>	_, Driller
				FORMA'	rion rec	ORD ON OT	THER S	IDE			
hereby s	swear or	affirn	n that the	information	given here	with is a o	complete	and cor	rect reco	rd of the wel	ll and all
ork done	e on it so	far :	as can be	determined i	irom availa	ble records.				-	
ubac-11	d en s					_	n -	<b>0</b> -	•		
uoscribed	and sw	orn to	before me	e this			Ulsa Place	, Okla	ahoma	Date	
ay of					., 19	Name_	<u>+</u>		300		
						Position	nD	ist.	dupt		

Notary Public

My Commission expires\_

Repollo Oil Company

Tulsa, Oklasoma

Representing\_

Address\_

FROM	то	THICKNESS	PORMATION RECORD FORMATION
0 310 495 605 1065 2475 2550 3412	310 495 605 1065 2475 2550 3412	IN FEET	Red rock Anhy Red beds Salt Anhy Lime and anhy Lime Total depth
		,	
			• • • • • • • • • • • • • • • • • • •
			• •