

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NMC-2748

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gisler "B"

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson (GB-SA)

11. SEC., T₅ R., S., OR BLK. AND
SURVEY OF AREA

Sec. 23-17S-30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

WINDFOHR OIL COMPANY

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE

1202 First National Bank Bldg., Fort Worth, Texas 76102

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)At surface 1950' f. south & 990' f. east lines of
Sec. 23-17S-30E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Plug back & re-complete

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Work started on Jan. 25, 1971. Plugged off Abo formation with 35 sacks cement containing 1/4# flow seal/sack. Spotted plug from 6832 to 6932'; set drillable bridge plug at 3300' with cement back to 3290'. Perforated 4 1/2" casing with 2 shots at 3278'. Could not circulate behind pipe. Perforated with 2 shots at 3212'. Could not circulate behind casing. Perforated Grayburg sands (Premier) from 3084-88 with 4 holes, 3104-10 with 6 holes and 3145-54 with 27 holes. Acidized with 500 gals. Well flowed 69 barrels of oil plus 1 barrels of water in 24 hours. (1-27-71)

RECEIVED
JAN 29 1971
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ralph L. Gray

TITLE Consulting Engineer.

DATE Jan. 28, 1971

(This space for Federal or State office use)

APPROVED BY

John A. Kraut

TITLE DISTRICT ENGINEER

DATE JAN 29 1971

CONDITIONS OF APPROVAL, IF ANY: