

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TRIPLICATE*
(Other Instr. is on re-
verse side)Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC 029020(b)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Atlantic Richfield Company ✓		8. FARM OR LEASE NAME Dale H. Parke "B" Tr. A	
3. ADDRESS OF OPERATOR P. O. Box 1978, Roswell, New Mexico 88201		9. WELL NO. 5	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FSL & 990' FWL (Unit letter L)		10. FIELD AND POOL, OR WILDCAT Jackson - Abo	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23, T17S, R30E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3665' GR		12. COUNTY OR PARISH Eddy	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well has been shut in since April 12, 1971 when production dropped to 1/2 BOPD. No remedial or recompletion prospects exist and we propose to P & A as follows:

Load hole w/salt gel mud.

Set 4½" 11.6# CIBP @ approx 6800' & cap w/2 sx cement.

Spot 20 sk cement plug in 4½" csg from 2350-2125' to cover squeeze perforations at 2298'.

Place 10 sx cement in top of well.

Erect dry hole marker, clear & level location.

The 8-5/8" & 4½" casing strings were cemented to the surface and will remain intact. Gel mud will be used to spot all cement plugs.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. L. BEEKMAN

TITLE

Dist. Drilling Supervisor

DATE

3/29/72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

APPROVED

MAR 30 1972

R. L. BEEKMAN

DISTRICT ENGINEER