

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>Water Injection</u>		5. LEASE DESIGNATION AND SERIAL NO. <u>LC-029339-A</u>
2. NAME OF OPERATOR <u>MINDEOHR OIL COMPANY</u>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <u>1202 First National Bank Bldg., Fort Worth, Texas 76102</u>		7. UNIT AGREEMENT NAME <u>Grayburg Jackson S.A.</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <u>440' from north and 1980' from east lines of Section 24-17S-30E.</u>		8. FARM OR LEASE NAME <u>Grayburg Jackson, CB-SA</u>
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	9. WELL NO. <u>4</u>
		10. FIELD AND POOL, OR WILDCAT <u>Grayburg Jackson, CB-SA</u>
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec. 24-17S-30E</u>
		12. COUNTY OR PARISH <u>Eddy</u>
		13. STATE <u>New Mexico</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) <u>Convert to Water Injection</u> ☒	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

An umbrella bridge was set at 3366'. Gravel was dumped from 3366' to 3357'. Cal seal was placed from 3357' to 3345'. On July 8, 1969, a 4½" O.D. 9.5# J-55 liner was cemented from 3345' to 2839' with 120 sacks of Incor cement. Top of liner was tested with 1500 psi. for 30 minutes and pressure held. Plugs were drilled out and hole cleaned out to 3568' on July 11, 1969. 2-3/8" O.D. upset tubing internally lined with cement was run and a tension packer was set at 2861'. Water injection was resumed on July 18, 1969.

RECEIVED

RECEIVED
JUL 25 1969
U.S. GEOLOGICAL SURVEY
FEDERAL BUREAU OF RESEARCH

18. I hereby certify that the foregoing is true and correct

SIGNED Ralph L. Gray TITLE Consultant DATE July 25, 1969

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY

ACCEPTED FOR RECORD PURPOSES ONLY
JUL 28 1969
Date
ACTING District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.