clst

Form 3160-5 (June 1990)

Conditions of approval, if any:

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

Lease Designation and Serial No. LC 029339A

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORT ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA,, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. [X] Oil Well [] Gas Well [] Other Jackson A #9 2. Name of Operator 9. API Well No. Burnett Oil Co., Inc. 30-015-04309 3. Address and Telephone No. 817/332-5108 801 Cherry Street, Suite 1500, Fort Worth, TX 76102 10. Field and Pool, or Exploratory Area Grayburg-Jackson 4. Location of Well (Footage, Sec., T., R., M., or Survey Description 11. County or Parish, State Unit B, 440' FNL, 1980' FEL, Sec. 24, T17S, R30E Eddy County, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION [] Notice of Intent [] Change of Plans [] Abandonment [] New Construction [X] Recompletion [X] Plugging Back [] Non-Routine Fracturing [X] Subsequent Report [] Casing Repair [] Water Shut-Off [] Altering Casing [] Conversion to Injection [X] Other CHANGE NAME TO JACKSON A #9 [] Dispose Water [] Final Abandonment Notice (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 3/03-10/97 Prepared location, repaired or replaced bad 7" casing, tested 7" casing to 300# for 15 mins.- held ok. Made chart for NMOCD. Ran GR/CNL/CCL/CBL, ran & set CIBP @ 3340', dumped total 35' cement on top of plug, PBTD now 3305'. Perforated total 20 holes, 1SPF @ 2831',36',43',48',49',51',60',76',80',87',99',2900',03',18',32',46',63',79',3001',3013' w/3-1/8" select fire casing gun. 3/12-17/97 Set RBP @ 2893', squeezed off perforations 2831'-2887' w/5 sks premium cement w/3/10% Halad 9, 2% CaCl. Drilled out cement 2629' to 2887', stopped back flow, perforated 2906',17',19',34',50',65',80',3000',02',3016', ran 4 1/2" packer. 3/18/97 Treated open perfs. 2899'-3016' w/1500 gals 15% HCL average PSI 2450# & ball out w/21 balls. 3/19-4/30/97 Swab tested and flowed well to test tank. All production is water. 5/1-7/97 POOH w/test tubing, ran 92 jts 2 3/8" cement-lined tbg, packer set @ 2869', laid flowline to Jackson A tank battery & turned well to battery flowline. 14. I hereby certify that the foregoing is trile and correct Petroleum Engineer (This space for Federal or State office Use) Date Approved by

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any False, Fictitious or fradulent statements or representations as to any matter within its jurisdiction.