

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN PLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-030570 B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection Well		7. UNIT AGREEMENT NAME Grayburg-Jackson Unit
2. NAME OF OPERATOR Anadarko Production Company		8. FARM OR LEASE NAME Tract 13
3. ADDRESS OF OPERATOR P. O. Box 260, Artesia, N. M.		9. WELL NO. 25-5
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 660' FWL Sec. 25 T-17S R-30E Eddy County, N. M.		10. FIELD AND POOL, OR WILDCAT Grayburg-Jackson
14. PERMIT NO. R-2323 WFX169		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25, T-17S, R-30E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3568' GR		12. COUNTY OR PARISH Eddy
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Convert to Water Inj.	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Cleaned well out to 3,300' with reverse circulator. Ran Gamma-Ray Neutron and Caliper logs.

Ran 230' 5 1/2" O.D. 8rd 15# csg for liner and set from 3,295' to 3,065' and cemented with 250 sx cement.

Perforated with abrasijet tool two (2) holes per ft at 3,222', 3,224', 3,248', 3,250', 3,252', 3,268'. Commenced water injection May 1966. 5 1/2" Larkin packer set at 3,085'. Water injection via 2" tubing below packer.

Final Report

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED E. W. Rickey
(This space for Federal or State office use)

TITLE District Supt.

APPROVED BY R. L. Beckman
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
MAR 15 1967
R. L. BECKMAN
ACTING DISTRICT ENGINEER

RECEIVED
MAR 15 1967
U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO
DATE March 14, 1967

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.