

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
AUG 11 1982

SUNDRY NOTICES AND REPORTS OF WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Water Injection Well
2. NAME OF OPERATOR
General Operating Company ✓
3. ADDRESS OF OPERATOR Suite 1007 Ridglea Bank Bldg.
Fort Worth, Texas 76116
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 1980' FWL
AT TOP PROD. INTERVAL: Section 25-T17S-R30E
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* T.A. ☒ ☐
(other)

5. LEASE
LC-030570(b)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-
7. UNIT AGREEMENT NAME
Grayburg Jackson Unit
8. FARM OR LEASE NAME
Tract 13
9. WELL NO.
8
10. FIELD OR WILDCAT NAME
Grayburg Jackson Queen SA
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 25-T17S-R30E, NMPM
12. COUNTY OR PARISH | 13. STATE
Eddy | New Mexico
14. API NO.
Not Available
15. ELEVATIONS (SHOW DF, KDR AND WD)
3552' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

To comply with New Mexico Oil Conservation Division Rule 705-A, we propose to temporarily abandon Grayburg Jackson Unit Tract 13 Well No. 8 as a water injection well as follows:

- (1) Set cast iron bridge plug in 3½" OD casing at an approximate depth of 3200' to plug off casing perforations from 3300'-38'.
(2) Pressure test 3½" OD casing above bridge plug to 500 psi.
(3) Shut in well with casing loaded with inhibited fresh water.

This work is being scheduled for the week of August 2, 1982.

Subsurface Safety Valve: Manu. and Type None Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED C. W. Stumboffer TITLE Vice President DATE July 27, 1982

APPROVED (This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

AUG 10 1982
JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

RECEIVED
JUL 29 1982