

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-030570(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-

7. UNIT AGREEMENT NAME

Grayburg Jackson Unit

8. FARM OR LEASE NAME

Tract 13

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson
Quest-Grayburg-San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 26-T17S-E30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

General Operating Company

MAY 10 1973

3. ADDRESS OF OPERATOR

P. O. Box 877, Wichita Falls, Texas 76307 O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.
At surface

660 feet from south line and 1980 feet from east line of
Section 26.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3545 feet DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☒
☐
☐
☐

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

☐
☐
☐
☐
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

☐
☐
☐

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to place this inactive producing well in operation. Before activating, we plan to perforate a Premier sand stringer of the Grayburg formation found at a depth of 3242'-54' on the Lane Well. GRN log run on this well on March 16, 1968 and stimulate this new zone and the existing lower Premier sand perforations from 3268'-76' with 30,000 gallons of gelled KCl water and 40,000 pounds of sand that will be applied in two equal treatments separated by a temporary block of rock salt and moth balls.

This work will be commenced on May 4, 1973.

RECEIVED

MAY - 7 1973

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. W. Stumhoff
C. W. Stumhoff

TITLE

Partner

DATE May 2, 1973

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
MAY 9 - 1973

R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of packing of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection, looking to approval of the abandonment.