

Form 9-331a  
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

Land Office Las Cruces

Lease No. 1G-040520

Unit Ordovician-Bureau II

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<b>Subsequent Report of Sandell</b> <b>x</b>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Loce Hills, New Mexico February 5, 1955

Well No. 1-8 is located 990 ft. from N line and 530 ft. from E line of sec. 27

SW 1/4 SW 1/4 Sec. 27  
(1/4 Sec. and Sec. No.)

17-S  
(Twp.)

30-E  
(Range)

R1E1  
(Meridian)

Premier  
(Field)

Hddy  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 3691 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

PRODUCTION PRIOR TO TREATMENT: Pumped 6 MOPD. Total production 132,075 B.O.

RECORD OF RECOMPLETION:

1-18-55 Run Gilbertson G-2 H-W packer at 2840 and H-1 hydraulic anchor at 2530, using 2-1/2" EUE tubing. Loaded annulus with 95 B.O.

1-19-55 Grubbed tubing.

1-20-55 Fractured as follows: 16 bbls. crude oil; 37 bbls. kerosene heated to 112 deg; 1,000 gals. of 24 gravity refined oil containing 1 lb. sand per gal; 1,000 gals. with 1-1/2 lbs; and 8,000 gals. with 2 lbs. Flushed with 50 bbls. crude. Max. inj. press. 3300 psig; at end of flush 2400 psig, dropping to 1800 psig upon stopping pump. Total injection time 3 1/4 min. Load oil to recover 416 bbls.

Continued on page #2

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company GENERAL AMERICAN OIL COMPANY OF TEXAS

Address P. O. BOX 416

LOCO HILLS, NEW MEXICO

By R. J. Heard  
R. J. Heard  
Title Field Supt.