

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reenter to a different reservoir.

Use "APPLICATION FOR PERMIT --" for such proposals.

N.M. Oil Cons. Division
811 S. 1st Street
Artesia, NM 88210-2834

SUBMIT IN TRIPLICATE

1. Type of Well

2. Name AROC (TEXAS) INC
PO BOX 702373
3. Address TULSA OK 74170-2373

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

978' FSL & 2323' FEL, Unit O
Section 27 - T17S - R30E

5. Lease Designation and Serial No.

NM-0467934

Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Grayburg Jackson PSU

8. Well Name and No.

Tract No. 5

9. Well API No.

30-015-04362

10. Field and Pool, or Exploratory Area

GB Jackson, 7R-QN-GB San Andres

11. County or Parish, State

Eddy County, New Mexico

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

12.

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☒ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this zone.)*

03/15/00 RIH w/6 1/4" mill tooth bit. Drilled cement from surface to 122'. Circulated clean.

03/16/00 - Drilled cement from 122' to 1195'. Circulated clean. Drilled CIBP to 1199' & cement to 2916'. Circulated
03/25/00 clean.

03/27/00 Drilled cement from 2916' to 3080'. Drilled CIBP from 3080' to 3083'. Drilled & washed down to 3257' (TD).

03/29/00 RIH w/shoe, 1-4 1/2" 10.5# shoe jt(35.60') float collar & 75 jts 4 1/2" 10.5 csg. Set shoe @ 3251'. Cmted w/180sx
Halliburton Lite w/1/4# FloCele, 100sx Premium Plus Class C w/2% CC, circulated 3.5sx to surface. BLM witnessed job.

04/04/00 Perforated 3142' to 3250' (14holes). Acidized w/2500 gals 15% NEFE acid w/30 ball sealers.

04/05/00 RIH w/plastic coated tension pkr, 100 jts new 2 3/8" plastic coated (TK-70) tbq to 3075'. Set pkr & tested
for 30min - held good. Shut well in awaiting authorization to inject.

14. I hereby certify that the foregoing is true and correct.

Signed

Thallia Marshall
Thallia Marshall

Title

ACCEPTED FOR RECORD
PETER W. CHESTER

Date 06/02/00

(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Approved By

Title

Date

Conditions of approval, if any:

JUN 22 2000
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA