



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Los Cruces
Lease No. 060528
Unit Hudson-Rosson 2

DEC 20 1954

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of sand</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Loco Hills, N. M. December 15, 19 54

Well No. 6-2 is located 1450 ft. from MM line and 1450 ft. from E line of sec. 27

N. 1/4 Sec. 27 17-S 30-E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Premier 24th New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5624 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

RECORD OF PRODUCTION PRIOR TO TREATMENT: Pumped 2 BOPD.

RECORD OF RECOMPLETION:

- 11-12-54 Cleaned out to 3232. Ran Galbreath 2-2 packer at 3002 on 2-1/2" EUE tubing with 7 jts. (216') below and 2-1 hydraulic anchor & 98 jts. above. Loaded annulus with 98 bbl.
- 11-13-54 Treated as follows: 8 bbls. lense crude; 31 bbls. kero. heated to 130 deg; 1,000 gals. 24 deg. API refined oil heated to 110 deg. and containing 1 lb. sand per gal; 1,000 gals (heated) with 1-1/2 lbs; 8,000 gals. (heated) with 2 lbs. Flushed with 82 bbls. crude heated to 125 deg. Max. inj. press. 1500 psig, dropping to 1,000 psig on stopping pump. On vacuum in 1 hr 45 min. Total inj. time 45 min. Total load oil incl. annulus 460 bbls. Pailed 2-1/2" EUE.

RESULTS OF TREATMENT:

11-14-54 produced 75 bbls.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

(Continued on page 2)

Company GENERAL AMERICAN OIL CO. OF TEXAS

Address BOX 436

LOCO HILLS, NEW MEXICO

By R. J. Board
R. J. Board

Title Field Supt.