

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

The summary on this page is for the condition of the well at above date.

Commenced drilling January 27, 19 42 Finished drilling March 18, 19 42

(Denote gas by G)

No. 1, from 2783' to 2785' No. 4, from _____ to _____
 No. 2, from 3123' to 3125' No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

No. 1, from no water to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

[illegible]

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8"	470'	50	Halliburton		2 ton
7"	2873'	100	"		3 "

Heaving plug—Material ----- Length ----- Depth set -----
Adapters—Material ----- Size -----

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
	3 1/2" & 5"	Glycerine	120 qts.	3/19	3123'	3212'
	3 1/4" & 5"	"	100 "	3/26	3123'	3212'

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Cable tools were used from 0 feet to 3212' feet, and from _____ feet to _____ feet.

_____, 19____
 The production for the first 24 hours was 1
 _____ barrels of fluid of which 100 % was oil; _____ %
 emulsion; _____ % water; and _____ % sediment.
 Gravity, °Bé. _____
 If gas well, cu. ft. per 24 hours _____
 Gallons gasoline per 1,000 cu. ft. of gas _____
 Rock pressure, lbs. per sq. in. 100

B. Call	Driller	M. A. Lapsley	Driller
B. Albert	Driller		Driller

FROM	TO	TOTAL FEET	FORMATION
0	108	105	Gyp
105	170	65	Red beds
170	190	20	Gyp
190	210	30	Anhydrite
210	225	15	"
225	300	75	"
300	345	45	Sandy shale
345	380	35	Anhydrite
380	420	40	Red beds
420	430	10	Anhydrite
430	445	15	Red beds
445	457	17	Anhydrite
457	1160	703	Salt
1160	1170	10	Anhydrite
1170	1205	35	" & shale
1205	1300	95	"
1300	1325	25	" & lime
1325	1380	55	" & shale
1380	1415	35	" sandy
1415	1450	35	" sandy shale
1450	1470	20	Red rock & sandy shale
1470	1520	50	Anhydrite & shale
1520	1630	110	"
1630	1745	115	" & shale
1745	1880	95	"

(OVER)

~~SECRET~~

FOKIA LION RECORD—continued

UNITED STATES SENATE
COMMITTEE ON LABOR AND PENSIONERS' BENEFITS
HEARING ROOM

LEW SAC MO TO 201

[illegible]

The information given herewith is a complete and correct record of the well and all work done thereon as far as can be determined from all available records.

Location: In the [N.] { } of [E.] { } of [W.] { } of [S.] { } of [T.] { } of [R.] { } of [C.] { } of [St.] { } of [Co.] { } of [U.S.] { }

Well No. []

Owner: []

Operator: []

Inspector: []

State: []

County: []

Township: []

Range: []

Section: []

Address: []

Company: []

which tends to flow out to portland and not to sea port and, consequently, will

OF OR HAS HANDS OR FINGER

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

HISTORY OF OIL OR GAS WELL

U. S. GOVERNMENT PRINTING OFFICE

FROM-	TO-	TOTAL FEET	FORMATION
1840	1890	50	Anhydrite & lime
1890	1920	30	"
1920	1955	35	" & lime
1955	1960	5	oil show
1960	2000	40	Anhydrite
2000	2050	50	" & lime
2050	2165	115	" , shale & lime
2165	2215	50	" & lime
2215	2240	25	" & shale
2240	2295	55	"
2295	2315	20	lime & shale
2315	2370	55	Anhydrite & shale
2370	2405	35	red sand
2405	2425	20	Anhydrite
2425	2460	35	lime
2460	2500	40	" & anhydrite
2500	2560	60	"
2560	2580	20	" - sandy brown
2580	2655	75	Anhydrite
2655	2705	50	" & sand rock
2705	2715	10	"
2715	2725	10	lime
2725	2740	15	Brown sandy lime & shale breaks
2740	2775	35	" - sandy
2775	2790	15	" - grey
2790	2900	110	"
2900	3009	109	"
3009	3021	12	" - sandy
3021	3125	102	"
3125	3136	11	" - sandy oil show
3136	3177	41	" - sharp
3177	3200	23	" - sandy
3200	3207	7	" - pink
3207	3212	5	" - grey
3212			Total depth