SE

## (SUBMIT IN TRIPLICATE)

## **UNITED STATES**

## DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land (	Office Las.	Cruc	3.
Lease	Office <b>Les</b> No. 0289	36 ×	d
Unit .	L		

110::0= 0: ::::=:::	TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
	TO CHANGE PLANS	
	TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION	TO RE-DRILL OR REPAIR WEI	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
	TO SHOOT OR ACIDIZE	1 5
	TO PULL OR ALTER CASING.	
NOTICE OF INTENTION	TO ABANDON WELL	
	(INDICATE ABOVE BY CH	HECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
		April 30, 1952 , 19, 19
ociley 7-D	is located 165	50 ft. from (N) line and 990 ft. from (W) line of sec. 29
	. 29 17 S	S 30 E N.M.P.M.
(¼ Sec. and Sec. 1	No.) (Twp.)	(Range) (Meridian)
Premier	Bo	ddy New Mexico  (County or Subdivision) (State or Territory)
(Field)		(County or Subdivision) (State or Territory)
The elevation of tl	he derrick floor abov	ve sea level is 2 ft.
		DETAILS OF WODE
		DETAILS OF WORK
State names of and expe	cted depths to objective san	nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
		nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- nts, and all other important proposed work)
April 28 bove well an nd a ten sac lug was set rd thd casin ith heavy mu	3, 1952, 1130'  id a ten sack  ik cement plug  in the shoe of  ig was pulled,  id and a stand	of 7" 20# casing was pulled from the cement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24# the hole was filled top to bottom dard marker set in cement in collar
April 28 bove well an nd a ten sac lug was set rd thd casin ith heavy mu	3, 1952, 1130'  id a ten sack  ik cement plug  in the shoe of  ig was pulled,  id and a stand	of 7" 20# casing was pulled from the sement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24#
April 28 bove well an nd a ten sac lug was set rd thd casin ith heavy mu	3, 1952, 1130'  id a ten sack  ik cement plug  in the shoe of  ig was pulled,  id and a stand	of 7" 20% casing was pulled from the sement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24%, the hole was filled top to bottom dard marker set in sement in collar and cleaned off
April 28 bove well an nd a ten sac lug was set rd thd casin ith heavy mu	3, 1952, 1130'  id a ten sack  ik cement plug  in the shoe of  ig was pulled,  id and a stand	of 7" 20% casing was pulled from the sement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24%, the hole was filled top to bottom dard marker set in cement in collar and cleaned off.
April 28 bove well an nd a ten sac lug was set rd thd casin ith heavy mu nd the locat	a 1952, 1130'  id a ten sack  ik cement plug  in the shoe of  ig was pulled,  id and a stand  tion leveled a	of 7" 20% casing was pulled from the sement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24%, the hole was filled top to bottom dard marker set in cement in collar and cleaned off.
April 28 bove well an nd a ten sac lug was set rd thd casin ith heavy mu nd the locat	a 1952, 1130's id a ten sack ok cement plug in the shoe of ig was pulled, id and a stand tion leveled a	of 7" 20% casing was pulled from the sement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24%, the hole was filled top to bottom dard marker set in cement in collar and cleaned off.
April 28 bove well an ind a ten sac lug was set rd thd casin ith heavy mu ind the locat	a 1952, 1130's id a ten sack ok cement plug in the shoe of ig was pulled, id and a stand tion leveled a	of 7" 20% casing was pulled from the sement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24%, the hole was filled top to bottom dard marker set in cement in collar and cleaned off.
April 28 bove well and a ten saculug was set rd thd casing the heavy must be located. I understand that this	is plan of work must receive	of 7" 20% casing was pulled from the sement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24%, the hole was filled top to bottom dard marker set in cement in collar and cleaned off.  MAY 1986
April 28 bove well and a ten sad lug was set rd thd casing ith heavy mu and the locat  I understand that thi Company Relar Address Box 3	is plan of work must receive	of 7" 20% casing was pulled from the sement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24%, the hole was filled top to bottom dard marker set in cement in collar and cleaned off.  All 1986 approval in writing by the Geological Survey before operations may be commenced.
April 28 bove well an nd a ten sad lug was set rd thd casin ith heavy mu nd the locat  Company Relar Address Box C	is plan of work must receive	of 7" 20% casing was pulled from the sement plug was set at shoe of the 7" g was set at in the 7" stub. A cement of the 8 5/8" and 309' of 8 5/8" 24%, the hole was filled top to bottom dard marker set in cement in collar and cleaned off.  All 1986  Approval in writing by the Geological Survey before operations may be commenced.