

Dec. 1984

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

RECEIVED BY
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
DEC 11 1984

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-L for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Phillips Oil Company ✓
3. ADDRESS OF OPERATOR
Rm 401, 4001 Penbrook St., Odessa, Tx 79762
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit E, 1980'FN & 660' FW
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐	☐
FRACTURE TREAT ☐	☒
SHOOT OR ACIDIZE ☐	☒
REPAIR WELL ☐	☐
PULL OR ALTER CASING ☐	☐
MULTIPLE COMPLETE ☐	☐
CHANGE ZONES ☐	☐
ABANDON* ☐	☐
(other) ☐	☐

5. LEASE
LC-028784-93-B
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Burch BB Fed
9. WELL NO.
11
10. FIELD OR WILDCAT NAME
Grayburg-Jackson 7R-Q-Gb/SA
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 30, T-17-S, R-30-E
12. COUNTY OR PARISH
Eddy
13. STATE
New Mexico
14. API NO.
30-015-04390
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3607'GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-17-84: 3254'PTD RU WSU. Pulled rods & pump. Installed BOP. POOH w/2-3/8" production tubing. Checked TD w/wireline (3250'). Ran 7" csg scraper to 2900' WIH w/7" Elder pkr, set @ 2850'. Loaded tbg/csg annulus w/81 bbls 2% KCL wtr. Loaded tbg/csg annulus w/81 bbls 2% KCL wtr. Trtd SA open hole w/5000 gals 20% NEFE HCL. Last tstd: Pmpd 24 hrs, 2 BO, 2 BO, .5MCFG.
9-18-84: Swbd 4 1/2 hrs, 85 bbls acid and load water. Trt'd SA open hole w/32,000 gals 30# x-linked gelled KCL wtr w/57,000# of 20/40 mesh and. Flushed w/1000 gals 2% KCL wtr.
9-19-84: Well flwd back approx. 325 bbls load wtr. Tagged fill w/bailer @ 3124'. CO to 3254'. WIH w/RBP, set at 2890'. Tstd to 1000#. Spotted 15 bbls 10% acetic acid 2775'-2400'.

Subsurface Safety Valve: Manu. and Type n/a Set @ Ft.

18. I hereby certify that the foregoing is true and correct
SIGNED W. J. Mueller TITLE Sr. Engineering Specialist DATE December 4, 1984
(This space for Federal or State office use)
APPROVED BY [Signature] TITLE DATE
CONDITIONS OF APPROVAL

Carlsbad

9-20-84: Perf'd 7" csg 2558'-2850'. Trtd w/3500 gals 7 1/2% NEFE HCL. Well flwd back 35 BPH.
 9-21-84: Trtd Grayburg w/27,300 gals refined oil w/34,000# of 20/40 mesh sand; 18,000# 12/20 mesh sand.
 9-22 thru
 9-24-84: Bailed sand to 2890'. Ran 2 3/8" production tubing.
 9-25-84: Set 2 3/8" tbg @ 2993'. Ran 2" x 1 1/2" x 12' pump.
 9-26-84: Cleaned and leveled location.
 9-27 thru
 10-05-84: WO pumping unit and installation of pumping unit.
 10-6,7-84: Pumped 48 hrs, 198 BLO, 20 BLW.
 10-8 thru
 11-29-84: Pumped 24 hrs a day to rec all of load.
 11-30-84: Pumped 24 hrs, 34 BO, 10 MCFG, Ø BW, gravity 33, GOR 294 .
 Job complete.

