

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN
(Other than
verse side)

DATE

Form approved
Budget Bureau No. 1004-0
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC 028936-D

IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ Water Injection Well

2. NAME OF OPERATOR

Anadarko Petroleum Corporation

3. ADDRESS OF OPERATOR

P.O. Drawer 130, Artesia, New Mexico 88211-0130

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

330' FSL & 2310' FEL

NOV 23 '88

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3571' GL

ARTESIA, NEW MEXICO

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

XX

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. WIH with tubing to PBTD of 1960'. Circulated hole with 10# brine and salt gel mud.
2. Spotted 30 sx Class C cement with 4% CaCl at 1960'.
3. Tagged top of plug after 3 hrs. @ 1781'.
4. Perforated 4 squeeze holes @ 1250'. (100' below salt).
5. WIH with pkr and pressure against squeeze holes to 1000#. Established that cement top is above squeeze holes.
6. Spotted 35 sx Class C cement with 4% CaCl @ 1290'.
7. Tagged top of plug after 3 hrs. @ 1105'.
8. Perforated 4 squeeze holes @ 475'. (50' above salt).
9. WIH with pkr and establish pump in rate. Did not circulate.
10. Cement squeezed with 40 sx Class C cement with 4% CaCl. Did not find top of plug after 3 hrs.
11. Cement squeezed again with 50 sx Class C with 4% CaCl.
12. Tagged top of plug after 14 hrs. @ 311'.
13. Spotted 60' surface plug. Dug out around casing with backhoe and redi-mixed with 4 yards cement.
14. Cut off all casing and anchors below surface. Set dry hole marker. Cleaned location.

Note: Will rip and re-seed location and road within next couple of weeks.

18. I hereby certify that the foregoing is true and correct

SIGNED

Mike Braswell

TITLE Field Foreman

DATE

11/24/87

(This space for Federal or State office use)

APPROVED BY

CHIEF, MINERAL RESOURCES

TITLE

DATE

11/21/88

*See Instructions on Reverse Side