IVIN UIL CUNS. CUMMISSION DRAWER DD Lorn, approved. Budget Bureau No. 1004-4-1 ARTESIA NH 881 F. -- 1160-5 Nacober 1983) UN TO STATES Empires August 31, 1985 DEPARTMEN OF THE INTERIOR THE BILDER Formerly 9-331) BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir Use "APPLICATION FOR PERMIT." for such proposals.) 7. UNIT AGREEMENT NAME Water Injection Well OTHER 8. FARM OR LEASE NAME NAME OF OPERATOR Federal "M" Anadarko Petroleum Corporation S WELL NO. ADDRESS OF OPERATOR P.O. Drawer 130, Artesia, New Mexico 88211-0130
To Artes of Well (Report location clearly and in accordance with any State requirements.\*

See piso space 17 below)
At surface 1 88211-0130 10. FIELD AND POOL OR WILDCAT Loco Hills-Qn-GB-SA RECEIVED 11. SEC., T., B., M., OR BI.E. AND SURVEY OR AREA 330' FSL & 2310' FEL AUG - 4 1993 31-17S-30E 12. COUNTY OR FARISH 13. STATE 15 ELEVATIONS (Show whether DF, RT, GR. etc.) . . D. 14 PERMIT NO 3571' GL Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data RREQUENT REPORT OF : NOTICE OF INTENTION TO PULL OR ALTER LASING TEST WATER SHUT-OFF ALTERING CASING MILITIPLE COMPUETS PRACTURE TREAT SHOOT OR ACIDIZE CHANGE PLANS NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) PETAIR WELL 17 to serible proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \* 1. WIH with tubing to PBTD of 1960'. Circulated hole with 10# brine and salt gel mud. 2. Spotted 30 sx Class C cement with 4% CaCl at 1960'. 3. Tagged top of plug after 3 hrs. @ 1781'. 4. Perforated 4 squeeze holes @ 1250'. (100' below salt). 5. WIH with pkr and pressure against squeeze holes to 1000#. Established that cement top is above squeeze holes. 6. Spotted 35 sx Class C cement with 4% CaCl @ 1290'. 7. Tagged top of plug after 3 hrs. @ 1105'. 8. Perforated 4 squeeze holes @ 475'. (50' above salt). 9. WIH with pkr and establish pump in rate. Did not circulate. 10. Cement squeezed with 40 sx Class C cement with 4% CaCl. Did not find top of plug after 3 hrs. 11. Cement squeezed again with 50 sx Class C with 4% CaCl. 12. Tagged top of plug after 14 hrs. @ 311'. 13. Spotted 60' surface plug. Dug out around casing with backhoe and redimixed with 4 yards cement. 14. Cut off all casing and anchors below surface. Set dry hole marker. Cleaned location. Note: Will rip and re-seed location and road within next couple of weeks. 18. I hereby certify that the foregoing is true and correct DATE 11/24/87 TITLE Field Foreman (This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: Approved as to plugging of the well berg Liability under band is retilined until surface restoration in completed. \*See Instructions on Reverse Side

TITLE