

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN
(Other instructions
reverse side)

ATE*
1 re-

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.
LC 028936-D

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Anadarko Production Company	8. FARM OR LEASE NAME Federal L
3. ADDRESS OF OPERATOR P. O. Box 116 Loco Hills, New Mexico	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FWL 1290' FWL Sec. 31, T 17 S, R 30 E Eddy County, New Mexico	10. FIELD AND POOL, OR WILDCAT Loco Hills
14. PERMIT NO. D	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEMP 31-17-30
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH Eddy
	13. STATE N. M.

16. **7 1967**

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☒
SHOOTING OR ACIDIZING ☐
(Other) **Set Liner**

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Cleaned well out with reverse drilling unit, drilled bridge plug, deepened to 3027', ran GF and Caliper logs, set 393' 1 1/2" OD 10.5# liner from 3027-2634 with Brown top hanger and packer, cemented with 100 sx., circulated excess cement over top of liner, sand-drill perforated Loco Hills sand 2750-54 and 2762-70 2/ft. Treated well with 20,000 gal water plus 20,000# 20-40 sand. Washed out well, ran 2" tubing and 3/4" rods and pump, set pumping equipment and placed well on production. Work commenced on 3 October 1967 and completed on 10 October 1967. Well placed on production 14 October 1967. On 16 October 1967 tested 10 bbls. oil and 60 bbls. water.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

TITLE **District Superintendent**

DATE **10-18-67**

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED
OCT 19 1967
U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

RECEIVED
OCT 26 1967
U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.