

Form approved.
Budget Bureau No. 42-R1424.

back to a different reservoir.
proposals.)

New Mexico

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Cleaned out well to PBTD 3018. Ran tubing and packer and squeezed perforations 2750-69 with 125 sx. Class H cement to 3000 psi. After cement set 18 hours the cement plug was drilled out of the casing and tested to 1000 psi. Ran GR-Acoustic log, perforated Grayburg sand 3002-12. Ran 2½" tubing with packer and treated well with 1000 gal. 15% HCl acid, 35,000 gal. gelled water, 35,000# sand. Then pulled tubing and packer, ran production tubing, rods, & pump; set pumping unit, connected well head and flow line and put well on production on 9-11-72.

DATE _____

***See Instructions on Reverse Side**

APPROVED
 SEP 19 1972
 R. L. BEEKMAN
 ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.