

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back a well or to alter a reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

SEP 11 1980

2. NAME OF OPERATOR

Anadarko Production Company

O. C. D.

3. ADDRESS OF OPERATOR

P. O. Box 67, Loco Hills, New Mexico 88255

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FSL & 1650' FEL Sec. 31, T17S, R30E

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☒FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) Set Liner ☒

SUBSEQUENT REPORT OF:

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

SEP 5 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rig up pulling unit; pull rods and tubing.
2. Clean out junk with reverse unit.
3. Set 443' of 4½", 10.5#, ST&C liner from approx. 2725' to TD.
4. Cement liner.
5. Perforate Premier from 3053' - 3081'.
6. Acidize and fracture treat new perms.
7. Return well to production.

Note: Loco Hills will not be re-opened after the liner is set.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jerry E. Huckle TITLE Area SupervisorDATE September 4, 1980

(This space for Federal or State office use)

APPROVED BY: (Orig. Sgd.) PETER W. CHESTER TITLE ACTING DISTRICT ENGINEERDATE SEP 8 1980

CONDITIONS OF APPROVAL, IF ANY: