Form	9-38	1a
(Feb	. 1951))
Γ		

(SUBMIT IN TRIPLICATE)

	528935 18
Lease No.	222232
Unit	<u> </u>

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

30-015-04411

CUNDDY NOTICES A	AND REPORTS ON WELLS
OTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHOT-OF
OTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO CITATOR SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO SHOOT OR ACTUAL CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO PULL OR ALTER CASH	SUPPLEMENTAGE TIPLE
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MA	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
,	
	april 20 , 1954.
(K Bec. and Sec. No.) (Comp.) (Comp.) (Comp.)	nty or Subdivision) (State or Territory)
he elevation of the domination	· =-
DE? State names of and expected depths to objective sands; sho ing points, and	PAILS OF WORK we sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work)
State names of and expected depths to objective sands; sho ing points, and the salt, this will be say and top to bottom.	rails of Work waizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ly 500° of new 8 5/8° 24° Casing sains be set with 50 sacks of cement and
State names of and expected depths to objective sands; shoring points, and will set approximate. On top the selt, this will be approximate the sold top to bottom. Se will set approximate the loco fills Zone, this will be approximate the loco fills Zone, this will be approximate to bottom by	rails OF WORK wastes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ly 500° of new 8 5/8° 24° Casing mins be set with 50 sacks of cement and ly 2800° of new 7° 20° Casing through li be set in 100 sacks of cement and lalliburton oil well cementing to.
State names of and expected depths to objective sands; sho ing points, and on t op the salt, this will be salt, this will be approximate the loco will set approximate the loco wills Zone, this will heavy mud top to bottom by This well will be drill	rails OF WORK waizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ly 500° of new 8 5/8° 24° Casing sains be net with 50 sacks of cement and ly 2800° of new 7° 20° Casing through li be set in 100 sacks of cement and lalliburton Gil well Gementing Co. led to top of the Andreas Line and all
State names of and expected depths to objective sands; sho ing points, and on t op the salt, this will be salt, this will be a will set approximate the loco mills Zone, this will heavy and top to bottom by This well will be drill	rails OF WORK waizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ly 500° of new 8 5/8° 24° Casing sains be net with 50 sacks of cement and ly 2800° of new 7° 20° Casing through li be set in 100 sacks of cement and lalliburton Gil well Gementing Co. led to top of the Andreas Line and all
State names of and expected depths to objective sands; sho ing points, and will set approximate. On top the salt, this will be salt, this will be will set approximate the Loco Hills Zone, this will heavy and top to bottom by This well will be drill zones tested. A certified plat will be drill. A certified plat will be drill.	rails OF WORK waizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ly 500° of new 8 5/8° 24° Casing saing be net with 50 sacks of cement and ly 2800° of new 7" 20° Casing through li be set in 100 sacks of cement and lialliburton Gil well Cementing Co. ded to top of the Andreas Line and all ce furnished by a resistered surveyor, oval in writing by the Geological Survey before operations may be commenced.
State names of and expected depths to objective sands; sho ing points, and will set approximate the top the salt, this will be salt this will set approximate the loco mills zone, this wi heavy and top to bottom by This well will be drill zones tested. A certified plat will be drill inderstand that this plan of work must receive approximate the company holand sich sootley.	rails of Work waizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) Ly 500° of new 8 5/8° 24° Casing sains be set with 50 sacks of cement and Ly 2800° of new 7° 20° Casing through li be set in 100 sacks of cement and Halliburton Gil well Generating Co. Sed to top of the Andreas Line and all Se furnished by a registered surveyor, oval in writing by the Geological Survey before operations may be commensed.
State names of and expected depths to objective sands; sho ing points, and will set approximate the top the salt, this will be salt this will set approximate the loco mills zone, this wi heavy and top to bottom by This well will be drill zones tested. A certified plat will be drill inderstand that this plan of work must receive approximate the company holand sich sootley.	rails of Work waizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) Ly 500° of new 8 5/8° 24° Casing sains be set with 50 sacks of cement and Ly 2800° of new 7° 20° Casing through li be set in 100 sacks of cement and Halliburton Gil well Generating Co. Sed to top of the Andreas Line and all Se furnished by a registered surveyor, oval in writing by the Geological Survey before operations may be commensed.
State names of and expected depths to objective sands; sho ing points, and will set approximate. The will set approximate the loco mills zone, this will heavy and top to bottom. This well will be drill zone to bottom by this well will be drill zone to to bottom. A certified plat will be drill understand that this plan of work must receive approximate the loco in the local set of the local set	rails of Work waizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) Ly 500° of new 8 5/8° 24° Casing sains be set with 50 sacks of cement and Ly 2800° of new 7° 20° Casing through li be set in 100 sacks of cement and Halliburton Gil well Generating Co. Sed to top of the Andreas Line and all Se furnished by a registered surveyor, oval in writing by the Geological Survey before operations may be commensed.
State names of and expected depths to objective sands; showing points, and will set approximate. The will set approximate the loco mills zone, this will heavy and top to bottom. This well will be drill zones tested. A certified plat will be drill understand that this plan of work must receive approximate that this plan of work must receive approximate that the plan of work must receive approximate the plan of work must receive approximate the plan of work must receive approximate the plan	rails of Work waizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) Ly 500° of new 8 5/8° 24° Casing sains be set with 50 sacks of cement and Ly 2800° of new 7° 20° Casing through li be set in 100 sacks of cement and Halliburton Gil well Generating Co. Sed to top of the Andreas Line and all Se furnished by a registered surveyor, oval in writing by the Geological Survey before operations may be commensed.
State names of and expected depths to objective sands; showing points, and will set approximate the top the salt, this will be salt approximate the Loco mills Zone, this will be depth and top to bottom by This well will be drill zone tested. A certified plat will be drill inderstand that this plan of work must receive approximate the company Roland with sootley.	FAILS OF WORK waizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) 1y 500° of new 8 5/8 24 Casing mains be set with 50 sacks of cement and 1y 2800° of new 7" 20 Casing through 11 be set in 100 sacks of cement and 11 be set in 100 sacks of cement and 12 liburton oil well dementing to. 13 ed to top of the Andreas Line and all 25 furnished by a registered surveyor, 26 ovalin writing by the Geological Survey before operations may be commensed.