

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 060429
Unit Bascon #7

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|---|-------------------------------------|--|
| NOTICE OF INTENTION TO STOP DRILLING | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF |
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | | SUBSEQUENT REPORT OF REDRILLING OR REPAIR |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY |
| NOTICE OF INTENTION TO ABANDON WELL | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Leas Hills, New Mexico, June 9, 19 51

Well No. 6-F is located 2310 ft. from N line and 330 ft. from W line of sec. 31
NE 1/4, Section 31 17-3 30-3 NMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Leas Hills Blair New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3587 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

PRESENT TOTAL DEPTH: 2877'.

PRESENT PRODUCING ZONE: Leas Hills Sand from 2861-77'.

PRESENT DAILY POTENTIAL: Well flows 2.5 BOPD on gas lift.

CUMULATIVE PRODUCTION THRU MAY 31, 1951: 64,958 barrels.

PRESENT CASING RECORD: 8-3/8" OD 24# set at 636' with 50 sacks. 7" OD 20# set at 2764' with 100 sacks.

(Continued on Sheet -2-)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company GENERAL AMERICAN OIL COMPANY OF TEXAS

Address Box 416, Leas Hills, New Mexico

By R. J. Heard
R. J. Heard,
Field Supt.

WE PROPOSE TO DEEPEN THIS WELL AS FOLLOWS:

OBJECTIVE: Premier Sand.

NEW TOTAL DEPTH: Approximately 3130'.

ADDITIONAL CASING: Will run approximately 213' of 5-1/2" OD 14# liner from 2714' to 2927'. Liner will be hung at 2714' in 7" OD casing with a lead seal pack-off liner hanger and cemented with 75 sacks of cement.

PROPOSED SHOOTING PROGRAM: In the event that commercial production is indicated from the Premier Sand this zone will be shot with 200 quarts of solidified nitro-glycerin.

DRILLING OPERATIONS TO RESUME: On or about June 17, 1951 with a Company owned National Machine.

