

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 060529
Unit Beeson F

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Loco Hills, New Mexico, August 28, 1951

Well No. 7-F is located 990 ft. from N line and 330 ft. from E line of sec. 31

NE 1/4 Section 31
(1/4 Sec. and Sec. No.)

17-S
(Twp.)

30-E
(Range)

NMPM
(Meridian)

Loco Hills
(Field)

Eddy
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 3585 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On August 6, 1951, at TD 2995', we ran 305.54' of 5 1/2" OD 14# 8rd thrd casing as a liner hung from 2986.46' to 2992.00' with a Baash-Ross regular action type hanger with lead packing. Liner was cemented with 56 sacks of cement by the Denton Oil Well Cementing Company.

After standing cemented for 72 hours plug was drilled and shut-off tested by the bailing method.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company General American Oil Company of Texas

Address Box 416

Loco Hills, New Mexico

By R. J. Heard
R. J. Heard,
Title Field Supt.

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 060529
Unit Beeson F

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Loco Hills, New Mexico, August 28, 19 51

Well No. 7-F is located 990 ft. from N line and 330 ft. from E line of sec. 31

NE 1/4 Section 31 17-S 30-E NMPH
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Loco Hills Eddy New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3585 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On August 6, 1951, at TD 2995', we ran 305.54' of 5 1/2" OD 14# 8rd thrd casing as a liner hung from 2986.46' to 2992.00' with a Bensch-Ross regular action type hanger with lead packing. Liner was cemented with 56 sacks of cement by the Denton Oil Well Cementing Company.

After standing cemented for 72 hours plug was drilled and shut-off tested by the bailing method.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company General American Oil Company of Texas

Address Box 416

Loco Hills, New Mexico

By R. J. Heard
R. J. Heard,
Field Supt.

Title